

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 032450(a)  
Unit South Mattix Unit  
(#11)

SUNDRY NOTICES AND REPORTS ON WELLS

|   |                                     |   |  |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL.....                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |  |
| NOTICE OF INTENTION TO CHANGE PLANS.....            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     |                                     | SUBSEQUENT REPORT OF ALTERING CASING.....       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... |                                     | SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....  |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        |                                     | SUBSEQUENT REPORT OF ABANDONMENT.....           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    |                                     | SUPPLEMENTARY WELL HISTORY.....                 |  |
| NOTICE OF INTENTION TO ABANDON WELL.....            |                                     |   |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 11 is located 2310 ft. from N line and 330 ft. from E line of sec. 22

NE/4 Sec. 22 T-24-S R-37-E NMPM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Fowler-Fusselman Las New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft. To be furnished when determined at a later date.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill the above well to approximately 7900' with rotary tools and set casing as follows:

| Hole Size | Casing Size | Depth  | Cement  |
|-----------|-------------|--------|---|
| 17 1/2"   | 13-3/8"     | 300'   | 380 sx circulated to surface.   |
| 12 1/2"   | 9-5/8"      | 4,350' | Two stage to isolate salt section with staging tool set at top of salt (approx. 1050'). 1st stage: 375 sx 8% gel and 100 sx neat. 2nd stage: 150 sx neat. |
| 7-7/8"    | 5 1/2"      | 7,900' | 150 sx 4% gel plus 150 cu. ft. perlite and 100 sx neat.   |

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stanolind Oil and Gas Company

Address Box 68  
Hobbs, New Mexico

By Joseph J. Henderson  
Title Field Superintendent