



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Office Las Cruces
Lease No. 02450 (A)
Unit South Matrix

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED
NOV 18 1954

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPC	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPC	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPC	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPC	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

ILLEGIBLE

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 13 *S. Matrix Unit* is located 2310 ft. from NE line and 330 ft. from E line of sec. 22
NE 1/4 of SE 1/4, sec 22 T-24
(Twp.) (Range) (Meridian)
Powder-Pusselman Las New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft. To be furnished later.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill the above well to approximately 7200' with rotary tools and set casing as follows:

Hole Size	Casing Size	Depth	Cement
17 1/2"	13-3/8"	300'	380 sx circulated to surface
12 1/2"	9-5/8"	4350'	Two stage to isolate salt section with staging tool set at top of salt (approx. 1950.) 1st stage: 375 sx 8% gel plug 100 sx neat. 2nd stage: 150 sx neat. 150 sx 4% gel plus 150 cu. ft. perlite and 100 sx neat.
7-7/8"	5 1/2"	7900	

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stanolind Oil and Gas Company
Address Box 68
Hobbs, New Mexico

By Lester W. Shaw
Title Field Engineer