

AREA 640 ACRES LOCATE WELL CORRECTLY NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

AUG 8 - 1940 HÓBBS OFFICE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE,

Drilling commenced 2-27-40 Name of drilling contractor Parker Drilling Co., Address Tulsa, Ok Elevation above sea level at top of casing 3227¹ feet. The information given is to be kept confidential until ? 19 GAS XXX SANDS OR ZONES No. 1, from to No. 4, from to No. 2, from to No. 5, from to No. 3, from to No. 6, from to IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from to feet. No. 2, from to feet. No. 3, from to feet. No. 4, from to feet. CASING RECORD	Oklahoma 19 Lahoma
Well is 1980 teet south of the North line and 1980 feet west of the East line of 1980 feet west of 1	Oklahoma 19 Lahoma
If State land the oil and gas lease is No. Assignment No. If patented land the owner is. Address. If Government land the permittee is. The Lessee is. Call Oil Corporation Address. Address. Tulas, Drilling commenced 2-27-40 19 Drilling was completed 6-22-40 Name of drilling contractor Parker Drilling Co. Address. Tulas, Ok Elevation above sea level at top of casing 3227' The information given is to be kept confidential until. 7 GAS XXX SANDS OR ZONES No. 1, from No. 2, from to No. 5, from to No. 6, from to IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from Rotary hole to CASING RECORD	Oklahoma 19 Lahoma
If patented land the owner is	lahoma
If Government land the permittee is Gulf 011 Corporation Address The Lessee is Gulf 011 Corporation Address The Lessee is Gulf 011 Corporation Address From Section 2-27-40 19 Drilling was completed 6-22-40 Name of drilling contractor Parker Drilling Co., Address Tulsa, Ok Elevation above sea level at top of casing 3227' feet. The information given is to be kept confidential until 7 19 GAS XXX SANDS OR ZONES No. 1, from 3450' No. 4, from to No. 2, from to No. 5, from to IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from to feet. No. 2, from to feet. No. 3, from to feet. CASING RECORD	lahoma
The Lessee is	lahoma
Name of drilling contractor Parker Drilling Co., Address Tulsa, Ok Elevation above sea level at top of casing 3227' The information given is to be kept confidential until GAS XXX SANDS OR ZONES No. 1, from 10 No. 4, from to No. 2, from to No. 5, from to IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from to feet. No. 2, from to feet. No. 3, from to feet. No. 3, from to feet. No. 4, from to feet. CASING RECORD	lahoma
Name of drilling contractor 3227 feet. Elevation above sea level at top of casing 3227 feet. The information given is to be kept confidential until 7.19 GAS XXX SANDS OR ZONES 3600' No. 4, from 10. No. 1, from 10. No. 2, from 10. No. 3, from 10. IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. Rotary hole 10. Rotary hole 10. CASING RECORD	lahoma
The information given is to be kept confidential until GAS XXX SANDS OR ZONES No. 1, from 10	
No. 1, from to No. 4, from to No. 6, from to No. 3, from to No. 1, from to No. 1, from to No. 6, from to No. 1, from to No. 1, from to No. 1, from to to Mater inflow and elevation to which water rose in hole. No. 1, from to feet. No. 2, from to feet. No. 3, from to feet. No. 4, from to feet. CASING RECORD	
No. 1, from to No. 4, from to No. 5, from to No. 3, from to No. 3, from to No. 6, from to IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from to feet. No. 2, from to feet. No. 3, from to feet. No. 4, from to feet. CASING RECORD	
No. 2, from to No. 5, from to No. 6, from to IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. Rotary hole to feet. No. 2, from to feet. No. 3, from to feet. CASING RECORD KIND OF CUT & FILLED PERFORA	
No. 3, from to No. 6, from to IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. Rotary hole to feet. No. 2, from to feet. No. 3, from to feet. CASING RECORD KIND OF CUT & FILLED PERFORA	
Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from to feet. No. 2, from to feet. No. 3, from to feet. CASING RECORD KIND OF CUT & FILLED PERFORA	
No. 1, from to feet. No. 2, from to feet. No. 3, from to feet. No. 4, from to feet. CASING RECORD	
No. 2, from to feet. No. 3, from to feet. No. 4, from to feet. CASING RECORD KIND OF CUT & FILLED PERFORA	
No. 3, from to feet. No. 4, from to feet. CASING RECORD KIND OF CUT & FILLED PERFORA	
No. 4, from to feet. CASING RECORD WEIGHT THREADS KIND OF CUT & FILLED PERFORM	
WEIGHT THREADS KIND OF CUT & FILLED PERFORA	
OTTO TOO TOO TO THE THE PROPERTY OF THE PROPER	
	TED PURPOS
SIZE PER FOOT PER INCH MAKE AMOUNT SHOE FROM FROM FROM	1 - 022 - 02
72 2 mange willion 31.	
5/8" 28 8 Lapw. 1285'	
16 10 Smls. 3225'	
MUDDING AND CEMENTING RECORD	
SIZE OF SIZE OF HOLE CASING WHERE SET OF CEMENT METHOD USED MID GRAVITY	
/4" 13" 37' 35 Hall1burton	INT OF MUD USED
8-5/8 1285' 500 Hall1burton	· · · · · · · · · · · · · · · · · · ·
4" 6" 3225' 175 Halliburton	
Adapters—Material Size	:
RECORD OF SHOOTING OR CHEMICAL TREATMENT	
SIZE SHELL USED CHEMICAL TREATMENT EXPLOSIVE OR DEPTH SHOT	
SIZE SHELL USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED DEF	PTH CLEANED OUT
SIZE SHELL USED CHEMICAL TREATMENT EXPLOSIVE OR DEPTH SHOT	PTH CLEANED OUT
SIZE SHELL USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED DEF	PTH CLEANED OUT
SIZE SHELL USED EXPLOSIVE OR CHEMICAL TREATMENT BETT OR TREATED DEPTH SHOT OR TREATED D	PTH CLEANED OUT
SIZE SHELL USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED DEF	PTH CLEANED OUT
SIZE SHELL USED EXPLOSIVE OR CHEMICAL TREATMENT BY CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEPTH SH	PTH CLEANED OUT
SIZE SHELL USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED D	
SIZE SHELL USED EXPLOSIVE OR CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEPTH SHO	
SIZE SHELL USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED DEPTH SHOT OR TREATED DEPTH SHOT OR TREATED DEPTH SHOT OR TREATED OR TREATED DEPTH SHOT O	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DE	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED DEP	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEF Hydrochloric Acid 1000 6-22-40 3600' Results of shooting or chemical treatment RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet of the state of the special tests of deviation surveys were made, submit report on separate sheet of the state of the special tests of deviation surveys were made, submit report on separate sheet of the state of the special tests of deviation surveys were made, submit report on separate sheet of the state of the special tests of deviation surveys were made, submit report on separate sheet of the state of the special tests of deviation surveys were made, submit report on separate sheet of the state of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of deviation surveys were made, submit report on separate sheet of the special tests of	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEF RESUlts of shooting or chemical treatment. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet is to 100 USED Rotary tools were used from 1 feet to 1600 feet, and from 1600 feet to 1600 feet to 1600 feet, and from 1600 feet to 1600 feet to 1600 feet, and from 1600 feet to 1600 feet	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEF RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to TOOLS USED Rotary tools were used from feet to feet, and from feet to PRODUCTION Put to producing July 1, 1940 The production of the first 24 hours was barrels of fluid of which % was semulsion; % water; and % sediment, Gravity, Be	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE OR TREATED DEF Hydrochloric Acid 1000 6-22-40 3600' Results of shooting or chemical treatment RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet is tools used Rotary tools were used from feet to 3600' feet, and from feet to 2able tools were used from feet to feet to feet, and from feet to producing July 1, 1940 Phe production of the first 24 hours was barrels of fluid of which % was smulsion; % water; and % sediment. Gravity, Be Gallons gasoline per 1,000 cu. ft. of gas_ If gas well, cu, ft. per 24 hours 3,146,880 Gallons gasoline per 1,000 cu. ft. of gas_	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED CHEMICAL USED QUANTITY DATE OR TREATED DEF Hydrochloric Acid 1000 6-22-40 3600' Results of shooting or chemical treatment. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet is tools used from feet to 3600' feet, and from feet to 2600' feet, and from feet to 2700 feet, and from feet to 3600' feet, and f	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED SAPLOSIVE OR CHEMICAL USED QUANTITY DATE OR TREATED DEF RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to 3600 feet, and from feet to 2600 feet, and from fee	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED EXPLOSIVE OR CHEMICAL USED QUANTITY DATE DEPTH SHOT OR TREATED DEF Hydrochloric Acid 1000 6-22-40 3600' Results of shooting or chemical treatment RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to 3600' feet, and from feet to 2600 feet, and from feet to 1600 feet, and from feet to 1600 feet, and from feet to 1900 cut to producing July 1, 1940 Put to production of the first 24 hours was barrels of fluid of which % was smulsion; % water; and % sediment. Gravity, Be 16 gas well, cu, ft. per 24 hours 3, 146,880 Gallons gasoline per 1,000 cu. ft. of gas Rock pressure, lbs. per sq. in Shut in Pressure 1200#. EMPLOYEES	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL, USED EXPLOSIVE OR CHEMICAL USED QUANTITY DATE DEFTH SHOT OR TREATED DEF Results of shooting or chemical treatment RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to TOOLS USED Rotary tools were used from feet to 3600' feet, and from feet to Dable tools were used from feet to feet, and from feet to PRODUCTION Put to producing July 1, 1940 The production of the first 24 hours was barrels of fluid of which was smulsion; water; and seed seed seed water; and Gallons gasoline per 1,000 cu. ft. of gas. Rock pressure, lbs. per sq. in Shut 1n Pressure 1200#. EMPLOYEES DEFTH SHOT DEFTH	and attach hereto
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL, USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED DEFINENCY. Results of shooting or chemical treatment. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to 3600' feet, and from feet to 2600' feet, and from feet to 5600' feet, and from feet to 5600'. Put to producing July 1, 1940. The production of the first 24 hours was barrels of fluid of which % was mulsion; % water; and % sediment. Gravity, Be if gas well, cu, ft. per 24 hours 3,146,880 Gallons gasoline per 1,000 cu. ft. of gas. Rock pressure, ibs. per sq. in Shut in Pressure 1200*. EMPLOYEES Driller Driller	and attach hereto fee fee foe foe prilles
Results of shooting or chemical treatment. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to 3600' feet, and from feet to 3600' feet, and from feet to 10 fee	and attach hereto fee fee foe foe prilles
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED EXPLOSIVE OR QUANTITY DATE DEPTH SHOT OR TREATED DEF Hydrochloric Acid 1000 6-22-40 3600' Results of shooting or chemical treatment RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to TOOLS USED Rotary tools were used from feet to feet, and from feet to feet to feet, and from feet to producing July 1, 1940 Put to producing July 1, 1940 The production of the first 24 hours was barrels of fluid of which was mulsion; % water; and sediment. Gravity, Be. Gallons gasoline per 1,000 cu. ft. of gas- Rock pressure, lbs. per sq. in Shut 1n Pressure 1200*. EMPLOYEES Driller FORMATION RECORD ON OTHER SIDE Thereby swear or affirm that the information given herewith is a complete and correct record of work done on it so far as can be determined from available records.	and attach hereto fee fee fee for fee Drilles the well and all
RECORD OF SHOOTING OR CHEMICAL TREATMENT SIZE SHELL USED EXPLOSIVE OF QUANTITY DATE DEPTH SHOT OR TREATED DEF Hydrochloric Acid 1000 6-22-40 3600' Results of shooting or chemical treatment RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet to TOOLS USED Rotary tools were used from feet to feet, and from feet to Sable tools were used from feet to feet, and from feet to feet, and from feet to feet, and from feet to Sable tools were used from feet to feet, and from feet to feet	and attach hereto fee fee fee fee fee Totille the well and all J 23, 1940

Address Tulsa, Oklahoma. Box 661

• :	na istati	nam station in	PRMATION RECORD
FROM	то	THICKNESS IN FEET	FORMATION
O†	38' 163		Caliche Red bed
	470 630		Red bed & shells Red bed
	665 780	44004 0040000	Sand rock Red bed & shells
	860 915		Red bed & lime shells Red bed
	1065		Red bed & shells Anhyerite
·	1092 1115	e grandate ar artis	Sand Anhydrite, broken
	1252		Salt & anhydrite to find the control of
	1260 1352		Ambyerite & salt
	1370 1390 1611	51.4	Salt Anhydrite
	1815	a ao teor	Salt & ambydrite Salt, anhydrite & shells Salt & ambydrite
	195 <u>5</u> 1978	1	Anhydrite
	1996 2170	58.1 10	Anhydrite & salt Salt & anhydrite shells
	22 89 2300	Use a Co	Salt Anhydrite
	5210 5230		Anhydrite & gyp Lime & anhydrite
	2145 2460		Anhydrite The Company of the Company
	2502 2577		Anhydrite & gyp
	2690 2704		Anhydrite Broken lime
	2747 2941		Lime & anhydrite
	2978 3182	,	Lime & gyp
	3202 3230		Sandy lime Property and the same and the party was a second
	3241 3250		Lime Broken lime Gray & brown lime
	3253 3253	129	Gray lime Gray & brown lime
	3278 3287	.* .	Gray lime Gray & brown lime
	3290 3290		Ges sand Gray lime
*	3315	3 4. ··	Gas asand
	3326 3328		Gas sand Sandy lime
	3332		Gas sand Gray sand & lime
	3349		Gray sandy lime
	3325		Gray lime & Bentonite
	3371		Gray lime Sandy gray lime
	33/5 3 383		Sandy lime Lime
	3392		Line
	3393 3396		Gray sandy lime Gray lime
	3456 3473	:	Shale & lime
	3600		Limb TOTAL DEPTH
		:	GEOLOGICAL TOPS
			Anhydrite 970'
			Salt Base 2280' Yates 2480'
			Tates 2480' Enight 3170' Penrose 3290'
			Penrose 3290' Eunice Polomite 3450' Total depth 3600'
	~.		
			A page of the large and All 2 Miles and the large and All 2 Miles and the large and th
		e i	The state of the s
			the state of the s
		-	e de la companya del companya de la companya de la companya del companya de la co
			Section 2017
			green and the second of the se
			And the second of the second o
			en e
		,	
		100	The state of the s
			ggen in de la companya de la company
			Control of the second of the s
	***	,	The state of the s
:			
			A CONTRACTOR OF THE PROPERTY O

• •