TUPUCAT		(Form C-103) (Revised 7/1/52)
The comment with the delivery and the same	NEW MEXICO OIL CONSERVATION COMMISSION	
	Santa Fe, New Mexico	
	MISCELLANEOUS REPORTS ON WELL	RECEIVED

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work opposing dis pleted. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shiptoffs, result of plugging of result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. Specific addition wel instructions in the Rules and Regulations of the Commission. Her

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING	REPORT ON RESULT OF TEST	REPORT ON	
DRILLING OPERATIONS	OF CASING SHUT-OFF	REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other) PLUG BACK	

July 9, 1953 Hobbs, New Mexico (Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation	Plains-Knight
(Company or Operator)	(Lease)
(Contractor)	, Well No1
The Dates of this work were as follows:	-30, 1953
Notice of intention to do the work (was not) submitted on F	form C-102 on, 19,
and approval of the proposed plan (was not) obtained	(oroso our incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

See Attached Sheet

	(Company) (Title)
Approved: OIL CONSERVATION COMMISSION	I hereby certify that the information given above is true and complete to the best of my knowledge.
Oil & Gds Inspector (Name) JUL 7.0.1953	Position. Asst. Area Prod. Supt. Representing. GulfOll. Corporation Address

Spotted 115 sacks Trinity inferno slow set cement plug from 11,194' to 10,800' thru 8782' of 4-1/2" DP & 2412' 2-3/8" tubing. Displaced w/134 bbls mud. Max. pressure 1100#. Tagged top of cement plug at 10,809'. Circulated 2-1/2 hrs. Spotted cement plug at 10,450' to 10,400' w/20 sacks Trinity slow set cement thru 2412' of 2-3/8" tubing & 3048' of 4-1/2" DP. Displaced w/124 bbls mud. Went in hole w/8-3/4" bit & found cement plug at 10,400', not set up. Cleaned hole & conditioned mud to 10,800'. Spotted 30 sacks Trinity inferno slow set cement plug from 10,450' to 10,400' thru 2412' of 2-3/8" tubing on 8038' of 4-1/2" DP. Flushed w/123 bbls drlg. mud. Went in hole w/8-3/4" bit to 10,809'. Gement plug at 10,450' not set up. Conditioned hole & mud. Spotted 15 bbls fresh gel mud & 15 bbls water ahead of 50 sacks Reg Neat Cement plug at 10,450' flushed w/3 bbls water & 37-1/2 bbls mud. Checked top cement plug at 10,355'. Went in hole w/8-3/4" bit & 4-1/2" DP. .