

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, plugging, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. Additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 27, 1953  
(Date)

Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation

(Company or Operator)

Lillie

(Lease)

Leffland Brothers Company

(Contractor)

, Well No. 2 in the NW 1/4 NW 1/4 of Sec. 23

T. 24-S, R. 37-E, NMPM., Undesignated Pool, Lea County.

The Dates of this work were as follows: April 23 - 25, 1953

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,

(Cross out incorrect words)

and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 82 joints 3572' of 8-5/8" OD 32# J-55 SS Casing. Set and cemented at 3585' in 2 stages thru HOWCO DV tool at 3192'. 1st stage cemented w/125 sacks regular Neat Lonestar, plug pumped to 3494'. Maximum pressure 600#. Cemented 2nd stage w/2250 sacks 4% Gel Portland Lonestar cement. Plug pumped to 3192'. Maximum pressure 1200#. Cement circulated approximately 5 sacks.

After waiting over 30 hours drilled plug in HOWCO DV tool at 3192' & tested casing & DV tool w/1000# water pressure for 30 minutes. There was no drop in pressure. Drilled cement plug from 3492' to 3585', tested cement below casing shoe w/1000# pressure for 30 minutes, there was no drop in pressure.

After approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill ahead.

Witnessed by R. S. Runyon Gulf Oil Corporation Drilling Foreman  
(Name) (Company) (Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name R. S. Runyon

Position Asst. Area Prod. Supt.

Representing Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico

Roy Yarbrough  
(Name)  
Oil & Gas Inspector  
(Title)  
APR 27 1953  
(Date)