• بورون	an a						<u> </u>		n-	
		Property of the second se								En n
	a share the second s	the state and						// /	OCT.	
,	1997 - 1997 -				•			- Un		S. MA
ORM C-10	antan Milanda. Bulan kulo					- 25	ana an an ann an Annsa.	. He	OF The second	
JIGH CIT	N							-••	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	12 mill
:				NEV	V MEXICO	OIL CONSERV		COMMISS	SION	SIN U
						Santa Fe, New	Mexico			2
X										
							•			
						WELL REC	ORD			;
										:
							•			
						Commission, Santa				
						ys after completion the Commission. Inc				
J	AREA 640					TRIPLICATE. FORM PROPERLY FILLS		L NOT BE A	APPROVED	
LOO	ATE WELL									
•••••	Ful	lerton C	il Compa	any		Box H; E	lobbs, N	en Nexi	<u>.</u>	
immons	, et al	Company or	Operator Well No.	1	in N	W/4	Addr 25	ess	m 2h	S
)[E	, 1	N. M. P. M.,	Lan	glie-Mati	t ix Field	,	Lea		•••••	County.
/ell is9	90 fe	et south of	the North	line and	33 0fee	transit of the	🕱 line of	Sectio	on 25	••••••
						1 , <i>1</i>			•	
he Lesse	e is	Fullerto	n 011 Co	mp any		, d	Address]	Los.Ange	les, C	alif.
						ing was complete		-		
						д у , 4			•	•
	,				feet.					
				L.				10		
	manon Brie		pr connaci	Inter anomen				10		
					SANDS OR					
						4, from				
						5, from				
o. 3, fro	m	······	to	•••••	No.	6, from	••••	to		
				IMPOR'	FANT WATI	ER SANDS				
nclude da	ata on rate o	of water infl	ow and ele	vation to wi	hich water r	ose in hole.				
io. 1, fro	None			.to		fee	t			:
						fee				1
						fee				
J. 1, 110	· • • • • • • • • • • • • • • • • • • •	•••••••••••••••••••••					v			
				CA	ASING REC	ORD				
0T/77	WEIGHT	THREADS			KIND OF	CUT & FILLED	PERF	ORATED	-	
SIZE	PER FOOT	PER INCH	MAKE	AMOUNT	SHOE	FROM	FROM	то		RPOSE
-5/8#	24#	8	Ingstn	413	Baker	Left in hol	· · · · · · · · · · · · · · · · · · ·	ļ e	Surfac	e-csg.
				 						ر = ب
	l		-					+		
	 			<u> </u>						·····

MUDDING AND CEMENTING RECORD SIZE OF HOLE SIZE OF CASING NO. SACKS OF CEMENT WHERE SET METHODS USED MUD GRAVITY AMOUNT OF MUD USED

	7-5/8*	413	150	Halliburton		- Ceim	ented to surface
	I		<u> </u>	PLUGS AND ADAPT	ERS		
Heaving	g plug—Ma	terial		Length		Depth S	et
Adapter	rs — Mater	ial		8	Size		······
			RECORD OF S	HOOTING OR CHEM	MICAL TREA	ATMENT	
SIZE	SHEL	L USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
					1	1	
	1	1	• • • •	1	1	I	
Results							
		·····					
P 3				F DRILL-STEM AND			
i arill-s	stem or othe	er special te	sts or deviation sur	veys were made, subm	nit report on	separate sheet a	id attach hereto.
					• • • •		
				TOOLS USED			
				to 3600 fee	t, and from.		et tofee
				to 3600 fee	t, and from.		
				to 3600 fee	t, and from.		et tofee
Cable to	ools were u	sed from		to 3600 fee to fee PRODUCTION	t, and from.		et tofee
Cable to Put to r	ools were u producing	sed from	feet	to	t, and from. t, and from.	fe	et tofee
Cable to Put to p The pro	ools were u producing duction of	sed from the first 24	hours was	to 3600 fee to fee PRODUCTION , 19	t, and from. t, and from. f fluid of wh	fe	et tofee et tofee
Cable to Put to p The pro emulsion	ools were u producing duction of n; 	sed from the first 24 % wate	hours was	to 3600 fee to fee PRODUCTION , 19	t, and from. t, and from. of fluid of wh y, Be	ich	et tofee et tofee , was oil;%
Cable to Put to p The pro emulsion if gas w	producing producing pduction of n; <u></u> vell, cu. ft. p	sed from the first 24 % wate per 24 hours	hours was	to	t, and from. t, and from. of fluid of wh y, Be	ich	et tofee et tofee , was oil;
Cable to Put to p The pro emulsion if gas w	producing producing pduction of n; <u></u> vell, cu. ft. p	sed from the first 24 % wate per 24 hours	hours was	to	t, and from. t, and from. of fluid of wh y, Be	ich	et tofee et tofee , was oil;
Cable to Put to p The pro emulsion If gas w Rock pr	ools were u producing oduction of n;	sed from the first 24 % wate per 24 hours. per sq. in	hours was	to	t, and from. t, and from. of fluid of wh y, Be gasoline per	ich	et tofee et tofee , was oil;%
Cable to Put to p The pro emulsion if gas w Rock pr	ools were u producing duction of n; vell, cu. ft. p ressure, lbs.	the first 24 % wate per 24 hours per sq. in	hours was r; and	to	t, and from. t, and from. of fluid of wh y, Be gasoline per		et tofee et tofee , was oil;
Cable to Put to p The pro emulsion if gas w Rock pr	ools were u producing duction of n; vell, cu. ft. p ressure, lbs.	the first 24 % wate per 24 hours per sq. in	hours was r; and	to	t, and from. t, and from. of fluid of wh y, Be gasoline per		et tofee et tofee , was oil;%
Cable to Put to p The pro emulsion of gas w Rock pr W , E.	ools were u producing duction of n; rell, cu. ft. r ressure, lbs. E. Morr R. Pess	the first 24 % wate per 24 hours. per sq. in bhis	feet hours was r; and FORMAT	to	t, and from. t, and from. of fluid of wh y, Be gasoline per		et tofee et tofee , was oil;
Cable to Put to p The pro emulsion if gas w Rock pr W. E.	ools were u producing duction of n; vell, cu. ft. r ressure, lbs. E. Morr R. Peac	sed from the first 24 % wate per 24 hours per sq. in bhis flirm that t	feet hours was r; and FORMAT	to	t, and from. t, and from. of fluid of wh y, Be gasoline per		et tofee et tofee , was oil;
Cable to Put to p The pro emulsion if gas w Rock pr Rock pr E.	ools were u producing duction of n; vell, cu. ft. r ressure, lbs. E. Morr R. Peze y swear or a as can be o	sed from the first 24 % wate per 24 hours per sq. in his flirm that t determined t	FORMAT he information give from available reco	to	t, and from. t, and from. of fluid of wh y, Be gasoline per OTHER SID lete and corr		et tofee et tofee , was oil;% s
Cable to Put to p The pro emulsion if gas w Rock pr Rock pr E.	ools were u producing duction of n; vell, cu. ft. r ressure, lbs. E. Morr R. Peze y swear or a as can be o	sed from the first 24 % wate per 24 hours per sq. in his flirm that t determined t	feet hours was r; and FORMAT he information give	to	t, and from. t, and from. of fluid of wh y, Be gasoline per OTHER SID lete and corr		et tofee et tofee , was oil;% s
Cable to Put to p The pro emulsion if gas w Rock pr Rock pr E.	ools were u producing duction of n; vell, cu. ft. p ressure, lbs. E. Mor R. Pese y swear or a as can be o bed and swo	sed from the first 24 % wate per 24 hours. per sq. in bhis flirm that the determined for orn to before	FORMAT he information give from available reco	to	t, and from. t, and from. of fluid of wh y, Be gasoline per OTHER SID lete and corr		et tofee et tofee , was oil;

My commission expires July 31, 1950 Notary Public

	W-Mexico Date
Name JBD an ne	
Position	
Representing	•••••••••••••••••
AddressBox H; Hobbs, New Mexic	0

FORMATION RECORD

FROM	то	THICKNESS IN FEET	FORMATION
0 74 980 2142 2487 2640 2710 2867 3039	74 980 2142 2487 2640 2710 2867 3039 3572	74 906 1162 345 153 70 157 172 533	Sand & Red Bed Red Bed & Shell Salt & Anhydrite Lime & Anhydrite Lime Lime, Anhy, & Gypsom Anhydrite & Lime Lime.
		÷	
		·	
			· · · · · · · · · · · · · · · · · · ·
	•		
	• • • • • •		
	·		



.