

Form 9-881a  
(Feb. 1961)

APPROVED

Budget Bureau No. 42-R358.4.  
Form Approved. NMO 321613

1		

Subject in condition IN TRIPLICATE)

on reverse

UNITED STATES

J. L. GORDON

ACTING DISTRICT SUPERINTENDENT DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

1963 JUL 2 AM 10 13

Land Office Las CrucesLease No. 035548Unit C

JUN 26 1963

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO <del>Abandonment</del> Plugback and recomplate	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Jack 8-26

June 26

19 63

Well No. 1 is located 640 ft. from [N] line and 1780 ft. from [W] line of sec. 26NE 1/4 NE 1/4 Sec. 26

(1/4 Sec. and Sec. No.)

24-3

(Twp.)

37-3

(Range)

ROPER

(Meridian)

NE 1/4

(Field)

Los

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3209 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of piping points, and all other important proposed work)

ILLEGIBLE

The subject well is presently plug.

We propose to plug back and recomplate in the Jalisco Gas Pool in the following manner: Set CIPF on wireline at 3200' 1/2 inch cement on top; perforate 2672-75, 2704-06, 2834-60, 2871-73, 2950-54, 2992-96, 3026-30, 3048-52 & 3126-30 1/2 inch; sand fracture 1/10,000 lb sand in 10,000 gals gelled water (fluid loss additive to be used) using 80 ball sealers. Then run tubing and sand well in.

A subsequent report will be filed upon completion of this work.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil CompanyAddress Box 62Union, New MexicoBy SIGNED: J. L. GORDON1000-4 NMO-3 ABS FileTitle District SuperintendentPa n (H-100-1) Att-1000-2 Calif Oil-1000, 1000 - 1 each

Condition:

The setting of a bridge plug does not constitute permanent abandonment of the lower perforations. Should conditions warrant, at the time of permanent abandonment, the bridge plug must be drilled out and cement placed across all perforations.