

Form 9-381a
(March 1942)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **LC-032592(b)**

Lease No. **41682**

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, December 27, 1949

C. C. Fristoe (b) NCT-2

Well No. 2 is located 1980 ft. from N line and 660 ft. from E line of sec. 26

1E4 S31 Sec. 26
(1/4 Sec. and Sec. No.)

24S
(Twp.)

37E
(Range)

NMPM
(Meridian)

Angelle Mattix
(Field)

Lee
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 3178 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD: 3506 - Dolomite

9-5/8" casing cemented at 1254' w/ 800 sacks.

7" casing cemented at 3250' w/ 425 sacks.

Shot well w/ 200 qts. duPonts Sowe #1 (American Glycerine Co.)
3.05-3505. Cleaned out well to 3506 and ran 2" EUE tubing to 3479'.
On 8 hour test 12-23-49 well flowed 15.8 bbls. pipe line oil thru
1 1/2" choke. GOR 1250, Gra. 36.6

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Texas Company

Address Box 1270

Midland, Texas

By J. H. Crew

Title Dist. Supt.