## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Regulations of the Commission. Indicate nature of report by checking below: REPORT ON BEGINNING DRILLING OPERATIONS REPORT ON REPAIRING WELL ORT ON PULLING OR OTHERWISE ALTERING CASING REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL REPORT ON RESULT OF TEST OF CASING REPORT ON DEEPENING WELL X REPORT ON RESULT OF PLUGGING OF WELL Eunice New Mexico July-19-1939 OIL CONSERVATION COMMISSION Santa Fe, New Mexico. Following is a report on the work done and the results obtained under the heading noted above Opper Amerada Pet Corp R.J.Johnston \_\_\_\_\_Well No. \_\_\_\_ Lease of Sec. 27 ,T. 24 ...., R. 37 N. M. P. M., Mattix Field, Iea The dates of this work were as follows: Notice of intention to do the work was (Nation) submitted on Form C-102 on July-15- 1939 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.) DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED 7-5/8" 25# 8 Thd Second Hand Seam'ess Casing Was Set In This Well At 435' And Cemented By The Halliburton Method With 150 Sacks El Toro Cement-Job Competed At 11-A.M.-7-15-59. This Casing Was Allowed To Stand Undisturbed For 72 Hrs, The Casing And Connections Were Then Tested With 1200# Pump Pressure And Allowed To Stand Undisturbed For 30 Minutes, No Drop In Pressure Resulted So The Cement Was Then Drived Out Of The Casing And The Same Test Of 1200# Pump Pressure Was Again Applied To The Casing And Connections, And Allowed To Stand Undisturbed For 30 Minutes, No Drop In Pressure Resulted So The Drilling Was Then Resumed. Witnessed by Bob Franklin Sparkman & Rausch Drig Co. Tool Pusher Company I hereby swear or affirm that the information given above is true and correct, Subscribed and sworn to before me this Name day of..... Position Supt Representing Amerada Pet Corp Company or Operator My Commission expires 12-21-1940 Address Drawer-D-Monument New Mexico Remarks:

OIL & GAS INSPECTOR

Title

. -