

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions
verse side)

BUDGET BUREAU No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> <i>Water Injection</i>	5. LEASE DESIGNATION AND SERIAL NO. <i>NM-7486</i>
2. NAME OF OPERATOR <i>Continental Oil Company</i>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <i>P. O. Box 460, Hobbs, NM 88240</i>	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>990' FSL and 1650' FEL of Sec 29</i>	8. FARM OR LEASE NAME <i>Jack A-29</i>
	9. WELL NO. <i>4</i>
	10. FIELD AND POOL, OR WILDCAT <i>Chonglio Matrix 7R, 12S Queen</i>
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>Sec 29, T-24S, R-37E</i>
13. PERMIT NO.	12. COUNTY OR PARISH <i>Lea</i>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3278' df</i>	13. STATE <i>NM</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) *Squeeze cmt OH*PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plug back in open hole w/ pea gravel and sand to 3450'. Set Squeeze tool at 3250' and Squeeze OH w/ 200 sacks Class C Cement. Drill out plug and pressure test to 900 psi.

18. I hereby certify that the foregoing is true and correct

SIGNED *Thos. Dwyer*TITLE *Sr. Analyst*DATE *4-13-73*

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

APR 16 1973

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side