

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0321613

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

CONTINENTAL Oil Company

3. ADDRESS OF OPERATOR

Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

990' FSL & 330' FEL OF SEC. 29

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

JACK B-29

9. WELL NO.

10. FIELD AND POOL OR WILDCAT

LARKIE MATTIX
7-RIVERS QUEEN

11. SEC., T., R., M., OR S.W. AND
SURVEY OR AREA

SEC. 29 T-24S R-37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3258' DF

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

RUN SLOTTED LINER

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

~~RUN SLOTTED LINER~~
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In order to eliminate the sloughing of the open hole section it is proposed to run 350' of 4" flush joint 11.34# J-55 csg. to TD w/ bottom 200' slotted w/ 1/16" x 4" slots. Bottom of liner will be bull-plugged. Bottom of 5 1/2" csg. is @ 3248', TD 3560'. Liner will not be cemented.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

SR. ANALYST

DATE

9-30-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

USGS-5, Murch. d, File