NEW METCO OIL CONSERVATION COMMISSION

SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST

Operator	Sin	clair '	011 4	Gas Com	PARY		Lease	m H. H	arrison	aDa Mi		Vell	4	
Lo ca tion	Unit	L	Sec	29	Twp	24	S	Rge	37 1		County	L	N	
OI WEIT	Name of	f Reser	rvoir	or Pool	, -	e of H	. 1	ethod o			Medium or Csg)	C	hoke	Size
Upper Compl	Jalmat					Gas		Flow		Ce		EI	Paso	Chol
Lower Compl	lenglie	Matti	x			Ges		Flow		To	6	n	Page	Chol
						FLOW	TEST NO	. 1						
Both zon	nes shut-	-in at	(hou	, date):		1:00	P.M. M	urch 7,	1966					
):							Upper Completion		Low Compl	
				producin							x	_		
				st							. 04	_	141	
				• • • • • • •							*		Yes	1
Maximum	pressure	e d uri r	ng tes	st	• • • • •	••••	. .	• • • • • •	• • • • • •		436	_	157	,
				st								_	141	,
				est								_	157	,
Pressure	change	during	g test	(Maximu	m minu	s Mi ni	imum)	• • • • • •	• • • • • •	· · · · · <u>·</u>	243	_	16)
Was pres	sure cha	ange ar	ı in cı	ease or	a decr	ease?.		• • • • • •	• • • • • •		Decrease	_	Incr	.0000
Oil Prod	luction					Gas	Produc	tion P		on	21 3/4 ho			
						FLOW 1	TEST NO.	2			11		T	
Well ope	ened at ((hour,	date)	: 9:	45 A.M	. Marc	h 10, 1	966		c	Upper Completion		Low Compl	
Indi ca te	e b y (X	() th	ne zor	e produc	ing	• • • • •	• • • • • •	• • • • • •	•••••	••••-			X	
Pressure	at begi	lnning	of te	st	• • • • •	• • • • •	• • • • • • •	• • • • • •	• • • • • • •	••••-	434	<u>.</u> .	172	<u> </u>
Stabiliz	ed? (Yes	or No)	• • • • • • •	• • • • • •	• • • • •	• • • • • • •	• • • • • •	• • • • • • •	• • • • •	Yes		Yes	<u> </u>
Maximum	pressure	d uri n	ng tes	t	• • • • • •	• • • • •	• • • • • •		•••••	••••-	434		172	<u> </u>
Minimum	pressure	durin	ng tes	t	• • • • • •	• • • • •	•••••	• • • • • • •	• • • • • • •		434		90	<u>; </u>
Pressure	at conc	lusion	of t	est	• • • • •	• • • • •	• • • • • • •	• • • • • •	•••••	••••-	434		90)
Pressure	change	during	test	(Maximu	m minu	s Mini	mum)	• • • • • •	• • • • • •	• • • • •	0		82	<u>}</u>
Was pres	sure cha	inge an	incr	ease or	a decr	ease?.	• • • • • •				io change		Decre	1600
		hour,	date)	21	45 P.N			966 Pr	tal time oduction		5 hours	·	_	
Oil Prod During T		Gas b	bls;	Grav			Product ng Test			_MCF;	GOR			
Remarks_	Arm	sal to	st.											
								····	 ;					
hereby cnowledg	-	tnat	tne i	nio rmati	on ner	ein c o	1			•	to the b		•	y
Approved					19		ব্য ² শ	erator_	1	1 0	L & Gas Co	<u>~~~</u>	FV .	
New Mex	ico Oil	Conser	vatio	n Commis	sion		Ву	<u></u>	N.X	· Sm	ith		 	
у<			···				Tit	le_ Tec	ter - 0:	il Rep	orts & Gas	, Se	rvice	10
itle							Dat	e Mar	eh 14,	1966				

SOUTHEAST NEW MEXICO PACKER LEARAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized and for a minimum of two hours thereafter, provided however, that they need not remain shut-in more than 24 hours.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued until the flowing wellhead pressure has become stabilized and for a minimum of two bours thereafter, provided however, that the flow test need not continue for more than 24 hours.

è

- 5. Following completion of Flow Test No. 1, the well shall again be shutin, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the previously shut-in zone is produced.
- 7. All pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked with a deadweight tester at least twice, once at the beginning and once at the end, of each flow test.
- S. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the appropriate District Office of the New Mexico Oil Conservation Commission on Southeast New Mexico Packer Leakage Test Form Revised 11-1-58, together with the original pressure recording gauge charts with all the deadweight pressures which were taken indicated thereon. In lieu of filing the aforesaid charts, the operator may construct a pressure versus time curve for each zone of each test, indicating thereon all pressure changes which may be reflected by the gauge charts as well as all deadweight pressure readings which were taken. If the pressure curve is submitted, the original chart must be permanently filed in the operator's office. Form C-116 shall also accompany the Packer Leakage Test Form when the test period coincides with a gas-oil ratio test period.

		1-11-
-5-0-2,7,2-17-4,2-1		