

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

The Texas Co.-Anderson Prichard Oil Corporation Midland, Texas

Company or Operator State of N. M. Well No. 32A-1 in CSW¹/₄ NW¹/₄ of Sec. 32, T. 24-S

R. 37-E, N. M. P. M. Langlie Lea County.

Well is 1980' feet south of the North line and 1980' feet west of the East line of NW¹/₄ Section 32

If State land the oil and gas lease is No. B-148 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is The Texas Co.-Anderson Prichard O. C. Address Midland, Texas

Drilling commenced 4-11-1939 Drilling was completed 6-15-1939

Name of drilling contractor Uscan Drilling Co. Address Oklahoma City, Oklahoma

Elevation above sea level at top of casing XXXXXX 3252 feet at Derrick floor.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3414 to 3549 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
9-5/8	25.70	8	1 1/2	391'	Baker				
7"	22	8	3mls	3413'	Halliburton				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	9-5/8	408	200	Halliburton		
	7"	3414	300	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Sol. Nitro	250	5-8-39	3445-3517	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3549 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 6-15-1939 on Test

The production of the first 24 hours was 336 barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be. 34

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. G/O Ratio 2000

EMPLOYEES

C. C. Kinder Driller J. S. Galbraith Driller

Oscar Giles Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 26th day of June 1939

My Commission expires 6-1-41

Notary Public

Address P. O. Box 1270, Midland, Texas

Representing The Texas Company

Company or Operator

Address P. O. Box 1270, Midland, Texas

DUPLICATE

RECEIVED
JUN 20 1939
HOBBS OFFICE

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	20	20	Surface Sand
20	110	90	Red Sand & Red Beds
110	130	20	Sand & Gravel
130	200	70	Red Beds & Sand
200	350	150	Red Shells & Sand
350	410	60	Red Rock
410	515	105	Red Rock & Shells
515	580	65	Hard Sand
580	750	170	Sand & Red Beds
750	883	135	Red Rock & Shells
883	1100	215	Red Beds & Sand
1100	1390	290	Anhydrite
1390	1515	125	Anhydrite & Salt
1515	1540	25	Anhydrite
1540	2454	914	Anhydrite & Salt
2454	2529	75	Anhydrite, Potash & Gyp
2529	2720	191	Salt & Anhydrite
2720	2764	44	Anhydrite
2764	2820	56	Lime
2820	2845	25	Lime & Gyp
2845	2940	95	Lime
2940	2950	10	Sand
2950	3025	75	Sand & Lime
3025	3088	63	Lime
3088	3109	21	Lime & Gyp
3109	3125	16	Lime
3125	3138	13	Lime & Gyp
3138	3150	12	Lime
3150	3180	30	Lime & Sand
3180	3353	173	Lime
3353	3391	38	Lime & Sand
3391	3403	12	Sand
3403	3433	30	Lime
3433	3456	23	Lime & Sand
3456	3549	93	Lime

T. D. - 3549'

Deviation Tests as Follows:

400' - 00
 1200' - 00
 2150' - 00
 2700' - 20
 3220' - 10

LFS-DAT
 6-23-39