

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

July 25, 1939

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.
Gentlemen:

DUPLICATE

You are hereby notified that it is our intention to commence the drilling of a well to be known as _____

SKELLY OIL COMPANY

State "N"

Well No. 3 in CNE SW

Company or Operator

Lease

of Sec. 32, T. 24, R. 37, N. M. P.M., Mattix Field, Lea County.

N.

The well is 1980 feet (N.) ~~300~~ of the South line and 1980 feet (E.) (~~W~~) of the West line of Section 32 -

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. 5943, Assignment No. _____

If patented land the owner is _____

Address _____


If government land the permittee is _____

Address _____

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma

We propose to drill well with drilling equipment as follows:



The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: _____

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing OD	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
18"	16"	70#	S. H.	125'	Cemented	100
14 1/2"	13"	50#	S. H.	390'	Landed	
12"	10-3/4"	40#	S. H.	710'	Landed	
9 1/2"	8-5/8"	32#	S. H.	1180'	Cemented	200
8 1/2"	7"	27#	New	3425'	Cemented	150

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3435 feet.

Additional information: In cementing the 16" OD casing the cement will be circulated back into the bottom of the cellar. At the time the 8-5/8" OD casing is run and cemented the 13" and 10-3/4" OD casing shall be pulled.

Approved JUL 31 '39, 19 _____
except as follows:

Sincerely yours,

SKELLY OIL COMPANY

Company or Operator

By J. T. Penland
Position District Superintendent

Send communication regarding well to

Name Skelly Oil Company

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Roy Garbrough

Title OIL & GAS INSPECTOR

