

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-057509

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

G.L. Erwin B Fed. NCT-2

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

S-35, T-24-S, R-37-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P.O. Box 728 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface1980' FSL, 330' FEL, Section 35, Township 24-S,  
Range 37-E, Unit Letter I, Lea County, New Mexico.

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3161' (DF)

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Downhole Commingle

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

HMOCC Case No. 5421, Order No. R-4972

1. Kill Tubb-Drinkard zone with fresh water. Install BOP's.
2. Drill out CIBP @ 6182' and 6785'.
3. Perforate Tubb-Drinkard 2-7/8" OD casing w/1 JSPF @ 5774', 5784', 5811, 5832', 5846', 5863', 5874', 5881', 5921', 5925', and 5941'.
4. Acidize perforations 5774'-6052' w/9000 gals 15% NE Acid in 6 stgs of 1500 gal acid w/220 lb Benzoic Acid Flakes in 200 gals gelled brine water between stages.
5. Perforate Tubb-Drinkard string and Abd. McKee string w/1-JSPF from 7146'-7152'.
6. Run rods and pump in old McKee string.
7. Test and place on production.
8. Downhole commingle Fusselman and Tubb-Drinkard zones.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Asst. Dist. Supt.

DATE 12-16-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
DEC 17 1975GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side