

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

☒ GAS WELL ☐ OTHER

NAME OF OPERATOR

EXACO Inc.

ADDRESS OF OPERATOR

P. O. Box 728 - Hobbs, New Mexico 88240

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Well located 330' from the East line and 330' from the South
line of Section 35, T-24-S, R-37-E, Unit Letter B.

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3159' DF

5. LEASE DESIGNATION AND SERIAL NO.

LC-057509

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

-

8. FARM OR LEASE NAME

G. L. Erwin "B" Federal

9. WELL NO.

NCT-2

5

10. FIELD AND POOL, OR WILDCAT

Justis Fusselman North

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 35, T-24-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

☐
☐
☒

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following work on subject well has been completed:

1. Perforate 2-7/8" csg w/l JSPF from 6950' - 6962', 7010' - 7060'.
2. Acidized perforations 6950' - 7060' w/4000 gals. 15% NE acid in 10 - 400 gal. stages w/25# benzoic acid between stages.
3. Swab, test and place on production.
4. On 24 hr PT end 10:00AM September 7, 1971, pumped 48 bbls oil and 94 bbls water. Grav 38°, GOR 440, 23 - 36" SPM, 1-1/4" pump.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Assistant District
Superintendent

DATE September 8, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE 1971

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

GEOLOGICAL SURVEY
NEW MEXICO

RECEIVED

FEB 1 1971

U.S. DEPARTMENT OF COMMERCE
BUREAU OF ECONOMIC ANALYSIS