

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
TEXACO Inc.

3. ADDRESS OF OPERATOR
P. O. Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FEL & 2310' FNL
AT TOP PROD. INTERVAL: (Unit Letter 'H')
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) To: Downhole Commingle

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
MAR 28 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
NM 14218

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-

7. UNIT AGREEMENT NAME
-

8. FARM OR LEASE NAME

C.C. Fristoe 'B' Fed. NCT-2

9. WELL NO.

6

10. FIELD OR WILDCAT NAME Justis Bline-
bry; Justis Tubb-Drinkard; Justis
Fusselman, North

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35, T-24-S, R-37-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3178' (DF)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rig up. Pull rods & pump from Fusselman. Install BOP.
2. Clean out 2 7/8" Fusselman string to 7203'.
3. Perforate Blinebry Zone in Fusselman string w/2-JSPF from 5440' - 5450'.
4. Perforate Tubb-Drinkard Zone in Fusselman string w/2-JSPF from 5940' - 5950'.
5. Pump 500 gal. 15% NE Acid down Blinebry string & overflush w/20 Bbls. water f/communication.
6. Pump 500 gal. 15% NE Acid down Tubb-Drinkard string & overflush w/20 Bbls. water f/communication.

(Continued on attached sheet)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Asst. Dist. Supt. DATE 3-26-80

(This space for Federal or State office use)

APPROVED BY _____
CONDITION _____ ANY:

APR 7 1980

DISTRICT SUPERVISOR

TITLE _____

DATE _____

RECEIVED
MAR 31 1980

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

APPROVED SUBJECT TO MINOR APPROVAL - [Signature]

RECEIVED
OIL CONSERVATION DIV

RECEIVED
APR 15 1980
OIL CONSERVATION DIV

Form 9-331

C. C. Fristoe 'B' Fed. Nct-2 Well No. 6

(Continued)

7. Run 2 1/16" tubing in Fusselman string. Install pumping equipment.
8. Test & place on production as triple downhole commingle of Blinebry, Tubb-Drinkard, and Fusselman Zones. Utilize Blinebry string as vent string.