

A blank sheet of graph paper with a grid pattern. The grid consists of 10 columns and 8 rows of squares. A small, dark mark or smudge is visible near the top left corner, approximately at the intersection of the second vertical line from the left and the seventh horizontal line from the bottom.

Jack Frost

Santa Fe, New Mexico

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE.

Jack Frost
(Company or Operator)

Linsey Little
(Lease)

Well No. 1, in S. 1/4 of T. 24, R. 37, NMPM.
one-eighth tax Pool, or County.

Well is 1000 feet from North line and 500 feet from east line
of Section 36. If State Land the Oil and Gas Lease No. is.

Drilling Commerced 10-30, 19. 53 Drilling was Completed 1-25-54, 19. 54

Name of Drilling Contractor Frost and Lester

Address 510 Lower Main St. S.W., Dallas, Texas

Elevation above sea level at Top of Tubing Head 357.6 The information given is to be kept confidential until
in case of once, 19.

No. 1, from.....	312	to.....	3334	No. 4, from.....	3334	to.....	3374
No. 2, from.....	3340	to.....	3354	No. 5, from.....	33 2	to.....	33 0
No. 3, from.....	3354	to.....	33 4	No. 6, from.....	3404	to.....	3434
					3474		3434
					3486		3440

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 400 to 505 feet.
 No. 2, from 505 to 510 feet.
 No. 3, from 510 to 515 feet.
 No. 4, from 515 to 520 feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
5-5/8"	32	Used	302'	Leather	Leather	-	Drill core
5-1/2"	35	New	3167'	Leather	Leather	240	Drill core
2"	4	New	340'		Leather	-	Drill core

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	7-5/8	302	125	Wet Mix		
7-7/8	5-1/2	3167	300	Wet Mix		

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Get perfor to 1 1/2 feet from 3 1/2 to 3 3/4 o frac with eastern company
with 4000 gallons of fluid - 1 1/2 sec d in one round of frac per gallon.
Used 175 lb per acre grade of acid break down, and up on fluid to up.

Result of Production Stimulation..... o had no trouble, 1/2 sec off wire - 1 hour and
oil per hour flowing.

.....Depth Cleaned Out.....

BOARD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special test or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3447 feet, and from feet to feet.
 Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 2-1, 1954
 OIL WELL: The production during the first 24 hours was 144 barrels of liquid of which Clean % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 30
 GAS WELL: The production during the first 24 hours was 140,800 M.C.F. plus 144 barrels of liquid Hydrocarbon. Shut in Pressure lbs.
 Length of Time Shut in -

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.			T. Devonian		T. Ojo Alamo
T. Salt	105		T. Silurian		T. Kirtland-Fruitland
B. Salt	250		T. Montoya		T. Farmington
T. Yates	2704		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen	2120		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash.		T. Mancos
T. San Andres			T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn.			T.		T.
T. Miss.			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	40	40	Red bed	3313	3330	17	lime
40	505	465	Red bed	3330	3442	112	lime and sand
505	607	102	Red bed, anhy & gyp	3442	3456	14	lime and sand
607	3	331	Red bed, anhy & gyp	3456	3467	11	lime
931	1009	78	Red bed and anhy.				
1009	1180	171	Red bed and anhy.				
1180	1225	45	Salt, anhy & red bed				
1225	224	374	Salt, anhy.				
224	2360	70	anhy.				
2360	2445	55	anhy.				
2445	2445	30	anhy.				
2445	2475	30	anhy.				
2475	2523	48	anhy.				
2523	2544	21	anhy.				
2544	250	45	anhy.				
250	2634	44	anhy.				
2634	263	29	anhy.				
263	3000	37	anhy.				
3000	3040	40	lime and sand				
3040	3140	50	lime				
3140	3130	40	lime				
3230	3235	5	lime				
3235	327	3	lime and sand				
327	3274	7	lime				
3274	3313	3	lime and sand				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator J. H. Porter
 Name J. H. Porter
 Address 2222 1/2 St. N. Bldg. 1, Dallas, Texas
 Position or Title Superintendent