

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 032579 (e)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Federal

8. FARM OR LEASE NAME

Carlson B-1

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Langlie-Mattix - 7 Rivers

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

1-25S-37E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Westates Petroleum Company

3. ADDRESS OF OPERATOR

1600 Broadway, Suite 2360 - Denver, CO 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

UNIT F

SE/4 NW/4 Section 1-25S-37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3122 DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PUMP OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Casing is as follows: 13-3/8" - 29# @ 143 with 150 sacks
8-5/8" - 32# @ 2330 with 350 sacks
5 1/2" - 14# @ 3410 with 300 sacks

TD 3421 in Queen.

We propose to set a cast iron bridge plug @ 3390 capped with 35' of cement; fill the 5 1/2" casing with 9.5# brine containing 25 sacks of gel per 100 bbls. of water; set another bridge plug at approximately 2400 capped with 35' of cement; cut or shoot the 5 1/2" at approximately 2350 and pull same; set a bridge plug in the bottom of the 8-5/8" casing at about 2300 and cap this with 35' of cement; fill the 8-5/8" with gelled brine as above; set a bridge plug at approximately 1000' or the top of the salt and cap it with 35' of cement; cut or shoot above this plug and remove the balance of 8-5/8"; set a cemented plug in the shoe of the 13-3/8" surface pipe consisting of 25 sacks of cement and a 10-sack cement plug at the top of the surface pipe with regulation marker set therein.

AMENDMENT: 1. Conditions encountered during plugging operations may require changes in the approved plugging program.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Manager

DATE April 8, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side