

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons

20 ex 1980

Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Breck Operating Corp.

3. Address and Telephone No.

P. O. Box 911 Breckenridge, Texas 76424 (254) 559-3355

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1730' FNL & 330' FWL Sec. 1-25S-37E

5. Lease Designation and Serial No.

NMLC-032579E NM 93034

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Westates Federal #5

9. API Well No.

30-026-11390

10. Field and Pool, or Exploratory Area

Justis Blinebry

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Status of Well

- 13-3/8" 48# casing @ 170' cement circ.
- 9-5/8" 32# casing @ 1005' TOC 150'.
- 7" 23# & 20# casing @ 6050' TOC 4335'.
- CIBP @ 5260' w/10' of cement in top.
- Perfs 5041-5222'.

Proposed Procedure

- Dump bail 25' of cement on BP @ 5260'.
- Put CIBP @ 5030' w/35' of cement on top.
- Cut off 7" casing @ 4330'.
- Put cement plug 50' in and 50' out of sub.
- Put 100' plug from 1055' to 955'.
- Put plug from 13' to 3'.
- Cut off casing, weld on I. D. plate, & fill any rathole with fill dirt.
- Work to be done by June 1, 1998.

RECEIVED
1998 FEB 27 P 3:17
BUREAU OF LAND MGMT
HOBBS, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed Ernie Underwood

Title Engineering Technician

Date 2/23/98

(This space for Federal or State office use)

Approved by (ORIG. SGD.) ALEXIS D. SANCHEZ

Title ENGINEER

Date 2/23/98

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side