

WELL DATA INFORMATION

SECTION 35, TWS. 24 S., RNG. 37 E.

Texaco Erwin #9-P
Drilled 1999 TD 6400'

HOLE	CSG.	DEPTH	CEMENT	
11"	8 5/8"	1010'	525 sx	circulated
7 7/8"	5 1/2"	6400'	570 sx	TOC 3400'

Texaco Erwin #8-I
Drilled 1996 TD 8298'


HOLE	CSG.	DEPTH	CEMENT	
11"	8 5/8"	1000'	1428 sx	circulated
7 7/8"	5"	8298'	1175 sx	circulated

Texaco Erwin #6-P
Drilled 1990 TD 8895'

HOLE	CSG.	DEPTH	CEMENT	
14 3/4"	11 3/4"	958'	650 sx	TOC 20'
11"	8 5/8"	5050'	2200 sx	circulated
7 7/8"	5 1/2"	8895'	1975 sx	circulated

Texaco Erwin #10-I
Drilled 1997 TD 6383'

HOLE	CSG.	DEPTH	CEMENT	
11"	8 5/8"	1046'	525 sx	circulated
7 7/8"	5 1/2"	6383'	1400 sx	circulated



SECTION 35, TWS. 24 S., RNG. 37 E. (CONT)

Texaco Erwin #4-O
Drilled 1971 TD 7050'

HOLE	CSG.	DEPTH	CEMENT	
20"	13 3/8"	255'	350 sx	circulated
16"	9 5/8"	3469'	1050 sx	TOC 1875'
8 5/8"	2 3/8"	7447'	1924 sx	TOC 2800'
	2 7/8"	7449'	1924 sx	TOC 2800'
	2 7/8"	7093'	1924 sx	TOC 2800'
	2 3/8"	6195'	1924 sx	TOC 2800'

Notice of intent to P & A has been filed.

Texaco Erwin #5-P
Drilled 1971 TD 8360'

HOLE	CSG.	DEPTH	CEMENT	
20"	16"	238'	300 sx	circulated
16"	13 3/8 & 11 3/4"	3500'	900 sx	TOC 1925'
10 3/4"	2 7/8"	8150'	1800 sx	TOC 1600'
	2 7/8"	7248'	1800 sx	TOC 1600'
	2 7/8"	7250'	1800 sx	TOC 1600'
	2 7/8"	8150'	1800 sx	TOC 1600'
	1 1/2"	8359'	1800 sx	TOC 1600'