

SECTION 36, TWS. 24 S., RNG. 36 E.

Mark L. Shidler Inc. Ramsey #2-M
Drilled 1961 TD 8480'

HOLE	CSG.	DEPTH	CEMENT	
17 1/2"	13 3/8"	1008'	810 sx	circulated
12 1/2"	9 5/8"	3426'	325 sx	TOC 2150'
8 3/4"	7" & 7 5/8"	8480'	680 sx	TOC 3770'

Mark L. Shidler Inc. Ramsey #4-M
Drilled 1962 TD 8155'

HOLE	CSG.	DEPTH	CEMENT	
17 1/2"	13 3/8"	1000'	760 sx	circulated
12 1/4"	9 5/8"	3480'	350 sx	TOC 2295'
8 3/4"	7 5/8" & 7"	8155'	700 sx	TOC-TS 6440'

Arch Petroleum Ramsey #3-L
Drilled 1961 Original TD 8520', Plugback to 5510'

HOLE	CSG.	DEPTH	CEMENT	
17 1/2"	13 3/8"	997'	880 sx	circulated
12 1/2"	9 5/8"	3463'	730 sx	circulated
8 3/4"	7 7/8"	8520'	700 sx	TS 4380'
	4 1/2"	6954'	650 sx	C

Sq. leak in 7 7/8", 3416'-3569', circulated cement to surface, ran 4 1/2".