

OPERATOR U.S. Smelting + Mining		DATE Drilled 1963 PTA 1969	
LEASE Westate	WELL No. 9	LOCATION E Set 1 - 25 - 37	

* Hole loaded w/ Gel

surface plug

13 $\frac{3}{8}$ " casing set at 321 ' with 220 sx of C cement
Hole size 17 $\frac{1}{2}$ "

Plug
2295 - 2395

Plug
192 - 3292

9 $\frac{5}{8}$ " casing set at 2344 ' with 550 sx of C cement
Hole size 12 $\frac{1}{4}$ "

Plug 3597 - 3897

Pull from 4975 - + Plug

Perfs 6525 - 6590

plug back

5 $\frac{1}{2}$ " casing set at 7699 ' with 620 sx of C cement

Total depth 8522 ' Hole size 7 "

Cement at 5100

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
CHECK INSTRUCTIONS ON REVERSE SIDE

Form approved.
Budget Bureau No. 42 R1424
LEASE DESIGNATION AND SERIAL NO.
LC 032579 (e)
INDIAN ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Use and use this form for proposals to drill, plug, or deepen existing wells to a different reservoir.
Use APPLICATION FOR PERMIT for each proposal.

1. OIL, GAS, OR OTHER
WELL, OR WELL, OR OTHER

2. NAME OF OPERATOR

United States Smelting, Refining and Mining Company

3. ADDRESS OF OPERATOR

P. O. Box 1877, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See instructions to form.)
At surface

900' FNL & 1650' FNL of Sec. 1

14. PERMIT NO.

15. REVISIONS OTHER THAN REVISION OF PERMIT

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

SUBSEQUENT REPORT OF:

TEST WATER TO TOP

1. TEST OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRAC TURE TREAT

2. COMPLETELY COMPLETED

FRAC TURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDONMENT

SHOOTING OR ACIDIZING

ABANDONMENT

REPAIR WELL

CHANGE CLASS

OTHER

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS CLEARLY, STATE ALL RESULTS, and give pertinent dates, including estimated data of starting and proposed work. If well is directionally drilled, give subsurface location and measured and true vertical depths for all markers and record pertinent to this work.

Cut off 5 1/2" casing at 4975 feet and pulled same. Set cement plugs as follows:

35 sacks 4792' - 4802'
35 sacks 3597' - 3607'
35 sacks 3192' - 3202'
35 sacks 2295' - 2305'
10 sacks 20' - Surface

Hole was filled with Gelled Mud between plugs. Marker was erected and location ready for inspection. Well plugged and abandoned December 30, 1968.

ILLEGIBLE

18. APPROVED BY (Signature) DATE

19. APPROVED BY (Signature) DATE

APPROVED BY
CONDITIONS OF APPROVAL (If any)

Production Clerk

DATE 1-14-69

APPROVED

DATE

*See Instructions on Reverse Side

ADJ. DIST. ENGINEER