

RECORD OF PRODUCTION AND STIMULATIONDEVONIAN

Perforated 6996', 6997', 7000', 7011', 7012', 7017', 7030', 7031', 7033', 7091',
7092', 7093', 7099', 7100', 7101', 7102', 7111', 7112', 7113', 7114' w/1 JS (20 holes).

Treated w/250 gallons 15% MCA.

In 6 hours swabbed and flowed 35 BO.

Treated w/1000 gallons 15% MCA.

On OPT flowed 153 BOPD + 1 BWPD (based on 50 BO + 0.6 BW in 13 1/2 hrs.) thru 10/64
choke. FTP 300 psi.

DRINKARD

Perforated 6011', 6032', 6034', 6036', 6043', 6095', 6096', 6105', 6106', 6107', 6135',
6136', 6155', 6161', 6173' w/1 JS (15 holes).

Treated w/1000 gallons 15% MCA.

Treated w/7000 gallons lease crude + approximately 1000# 20 - 40 mesh sand + 350 #
Mar II Adomite.

On OPT flowed 113 BOPD + 2 BWPD (based on 95 BO + 1 BW in 10 1/4 hrs.) thru 24/64
choke. FTP 320 psi.

BLINDBAY

Perforated 5409', 5402', 5403', 5406', 5559', 5560', 5599', 5600', 5602', 5697',
5699', 5660' w/1 JS (12 holes).

Treated w/1000 gallons 15% MCA.

Treated w/15,000 gallons lease crude + approximately 14,000# 20 - 40 mesh sand
+ 750# Mar II Adomite.

On OPT flowed 420 BOPD (based on 50 BO in 3 1/4 hrs.) thru 16/64 choke, cut 0.35
B32W, FTP 600 psi.

LIST OF DEVIATION SURVEYS

95' = 2 deg.	4753' = 2 1/2 deg.	6201' = 1 1/4 deg.
2455' = 4 deg.	5016' = 3 deg.	6669' = 1 1/2 deg.
2612' = 4 deg.	5095' = 2 1/2 deg.	6793' = 1 1/2 deg.
2953' = 3 1/4 deg.	5230' = 2 1/2 deg.	
3153' = 3 deg.	5396' = 2 3/4 deg.	
3616' = 2 1/4 deg.	5565' = 1 1/4 deg.	
4045' = 2 3/4 deg.	5691' = 2 deg.	
4579' = 3 3/4 deg.	6092' = 1 1/2 deg.	