Submit 3 Copies to Appropriate District Office

State of New Mexico

Form C-103 Revised 1-1-89

DISTRICT P.O. Box 1980, Hobbs, NM 88240

DISTRICTII

Energy, Minicials	and Mannan McSo	urca Departuent
OIL CONSI	ERVATION	DIVISION

2040 Pacheco St. Santa Fe, NM 87505 WELL API NO. 30-025-11408

P.O. Drawer DD, Artosia, NM 88210	5. Indicate Type of Lease STATE FEE				
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lesse No. B-11302				
SUNDRY NOTICES AND REPORTS ON WELLS					
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name				
1. Type of Well: OIL OAS WELL WELL OTHER	New Mexico "BM" State				
2. Name of Operator Nadel and Gussman Permian, L.L.C.	8. Well No.				
3. Address of Operator 601 N. Marienfeld, Suite 508, Midland, TX 79701	9. Pool name or Wildcat Justis Blinebry				
4. Well Location P 915 South 33 Unit Letter : 915 Feet From The Line and	East Line				
Section 2 Township 25S Range 37E	Lea NMPM County				
10. Elevation (Show whether DF, RKB, RT, GR, etc.) . 3126 DF					
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING				
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING	G OPNS. PLUG AND ABANDONMENT				
PULL OR ALTER CASING CASING TEST AND C	EMENT JOB .				
OTHER: add Blinebry pay	🗆				

- 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
 - 1. MIRU. Set 4-1/2" BOP on east casing. Pull rods and pump. Pickup work string and casing scraper and TIH. Tag bottom at 7000' and check for fill. POH.
 - Rig up wireline. Run CBL from 7000' to 4000'. Selectively perforate the following Blinebry intervals @ 4SPF:
 - 4976' 5176' (25') & 5524' 5604' (13')
 - 3. Rig up coil tubing unit on 2-7/8" tubing (W). Spot 5 Bbls of 80# "Temp-Block" gel, or equivalent, across Blinebry
 - In 4-1/2" string, frac lower Blinebry perfs with 25,000# of 20/40 resin coat sand and linear gel at 7 Bbls/ Minute. Frac upper Blinebry perfs with 35,000# of 20/40 resin coat sand. POH with packer and pick up bit. Drill out sand and clean casing out.
 - 5. Rig down CT unit. Run pumping equipment and test.

I hereby certify that the	information above us true and complete to the best of my	knowledge and belief. Operations Engineer	DATE 8-11-99
TYPE OR PRINT NAME	Robert McNaughton		телетноке но. 915-6824429
(This space for State Use)		AUG 0 ~ 1999	
OF APPROVED BY	RIGINAL SIGNED BY CHRIS WILLIAMS DISTRICT I SUPERVISOR	TITLE	DATE

NADEL and GUSSMAN PERMIAN

New Mexico BM State #3

Unit P, Sec 2, 25S, 37E, Lea County NM API # 30-025-11408

