

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SAINTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR FILE BACK TO A DIFFERENT RESERVOIR. SEE "APPLICATION FOR PERMIT -" (FORM C-101, FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☐ Fee ☒ 5. State Oil & Gas Lease No.
1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER- 2. Name of Operator Mobil Producing TX. & N.M. Inc. 3. Address of Operator Nine Greenway Plaza, Suite 2700, Houston, Texas 77046 4. Location of Well UNIT LETTER <u>L</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>3</u> TOWNSHIP <u>25S</u> RANGE <u>37E</u> N.M.P.M.		7. Unit Agreement Name 8. Farm or Lease Name Liberty 9. Well No. 3 10. Field and Pool, or Wildcat Jalmat
15. Elevation (Show whether DF, RT, GR, etc.) 3159 GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WORK ☐ ALTERING CASING ☐ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐ PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐		SUBSEQUENT REPORT OF: OTHER ☐
---	--	--

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- GIH w/5-3/4-17#/ft cmt ret on work string, set ret @ 2950⁺
 - Sqz yates interval w50sx class C neat cmt
 - Pull out of ret and spot 10 sx cmt on retainer
 - WOC-2H₂ min.
 - Circ 9.5#/gal mud from 2850-surf (100 Bbl reqd)
 - Rig up casing jacks
 - Determine free pt of 5-3/16" casing
 - Spot cmt plug from 50 ft below to cut off point (5sx min)
 - GIH w/csg cutter-cut and pull all free 5-3/16 casing
 - GIH w/work string and spot cmt to 75 ft above casing stub (30-40sx)
 - Spot cmt from 950-1350 ft. to cover salt top and 9-5/8 csg shot (120 sx reqd)
 - Pull up to surf and spot 10 sx (min) plug at surface
 - Install monument
- Use only "Neat" Cement

Note: This procedure has been discussed with Mr. Jerry Sexton, NMOCD-Hobbs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>J. N. Heath</u>	TITLE <u>Authorized Agent</u>	DATE <u>12-6-82</u>
APPROVED BY <u>JERRY SEXTON</u>	TITLE <u>DISTRICT 1 SUPR.</u>	DATE <u>DEC 16 1982</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED
DEC 10 1982
G.C.A.
HOBBS OFFICE