

LEASE LIBERTY WELL NO. 3

ANNULAR FLUID PRIOR TO WORKOVER PRODUCED FLUID & GAS

W/O FLUID TO BE USED MUD WT.(LBS/GAL) 9.5 HYD. PRESS 494 PSI RES. PRESS -

① MIRU PULLING UNIT

② REMOVE PRODUCTION TUBING; GOOD TUBING TO BE USED FOR WORK STRING -
BAD TUBING TO KERMIT YARD FOR JUNK SALE

③ GIH w/ 5 3/16" - 17 #/ft CMT RET ON WORK STRING, SET RET @ 2950 ±

④ SO2 YATES INTEGRAL w/ 50 SX CLASS C NEET CMT

⑤ PULL OUT OF RET AND SPOT 10 SX CMT ON RETAINER

⑥ WCC - 2 HR MIN.

⑦ Circ 9.5 #/gal mud from 2850 - SURF (100 BBL @ 3000)

⑧ PULL UP CASING - JAIL

⑨ DE-EMULS FREE PT OF 5 3/16" CASING

⑩ SPOT CMT 2-UG FROM 50 FT BELOW TO CUT OFF POINT (5 SX MIN)

⑪ GIH w/ CSG CUTTER - CUT AND PULL ALL FREE 5 3/16" CASING

⑫ GIH w/ WORK STRING AND SPOT CMT TO 75 FT ABOVE CASING STUB (30-40 SX)

⑬ SPOT CMT FROM 950 - 1350 FT, TO COVER SALT TOP AND 9 5/8 CMT SHALE
(120 SX REQ)

⑭ PULL UP TO SURF AND SPOT 10 SX (MIN) PLUS AT SURFACE

⑮ INSTALL MONUMENT

MONUMENT SHALL BE STEEL PIPE 4" DIA AND 10 FT LONG; ORANGE PEELED
OR PLUGGED AT SURFACE END. A MINIMUM OF 4 FT SHOWING ABOVE G.L.

THE MONUMENT WILL HAVE THE FOLLOWING STAMPED OR WELDED TO IT

"MOBIL PRODUCING TEXAS & NEW MEXICO, INC.

LIBERTY 3 WELL, JAMES YATES GAS POOL

NW 1/4 OF SW 1/4, SEC 3, T25S, R37E

LEA COUNTY, NEW MEXICO

NOTE: THIS PROCEDURE HAS BEEN DISCUSSED WITH MR JERRY SEYMOUR,
NMOC - HOBBS. THEY SHOULD BE CONTACTED 24 HRS PRIOR
TO BEGINNING PLUGGING OPERATIONS

ICLR 9/82

DISTRIBUTION: MC FN CR 10/8/82 CR 10-15-82 10/15

RECEIVED
DEC 10 1982
S.C.D.
HOBBS OFFICE