



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Las Cruces**
Lease No. **055546**
Unit **Wells**

RO-770 **SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 27, 1955, 19

Well No. **3** is located **1980** ft. from **NE** line and **1980** ft. from **W** line of sec. **5**
C-WF/4 SW/4 Sec. 5 **25S** **37E** **NMPN**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Langlie-Mattix **Lea** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3218.5** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill to the approximate depth of 3350', set 250' of 9-5/8" casing (surface), cemented with 250 sacks cement to set 24 hours. Approximately 3250' of 7" casing to be set using 300 sacks neat cement, 2-staged cement to set 48 hours.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **R. OLSEN, Drawer RZ, Jal. New Mexico**
 Address **2811 Liberty Bank Bldg.**
Oklahoma City, Okla.

By *R. Olsen*
 Title *Manager*

111