	Budget Bureau 42-R358.3. Approval expires 12-31-55.		
Ld Office	Las Cruses		
Lease No.	055546		
** •	viells		

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS	SUNDRY	NOTICES AND	O REPORTS ON V	WELLS
Well No. 7. is located 1980 ft. from line and 1980 ft. from Well line of sec. 6 SE/A NW/A 253 37E NMPM (Well Bec. and Sec. No.) (Twp.) (Range) (Meridian) Langlia Mattix Lea (County or Subdivision) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work) We propose to drill to the approximate depth of 3500', set 300' 8 5/8" surface casing with 250 sx. cement to set 24 hrs. 3500' 52" 15.50% Oil string, cemented with 300 sx. cement, two staged, to set 48 hrs. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company R. OLSEN, Drawer Z, Jal, New Mexico	NOTICE OF INTENTION TO CHANGE NOTICE OF INTENTION TO TEST WA NOTICE OF INTENTION TO RE-DRILL NOTICE OF INTENTION TO SHOOT O NOTICE OF INTENTION TO PULL OR	PLANS TER SHUT-OFF OR REPAIR WELL OR ACIDIZE ALTER CASING	SUBSEQUENT REPORT OF SHOOTING O SUBSEQUENT REPORT OF ALTERING O SUBSEQUENT REPORT OF RE-DRILLING SUBSEQUENT REPORT OF ABANDONME	OR ACIDIZING
Well No	(INDIC	ATE ABOVE BY CHECK MARK NAT	URE OF REPORT, NOTICE, OR OTHER DAT	A)
SE/4 NW/4 25S 37B NAPK (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Langlie Mattix Lea (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme ing points, and all other important proposed work) We propose to drill to the approximate depth of 3500', set 300' 8 5/8" surface casing with 250 sx. cement to set 24 hrs. 3500' 52" 15.50% Oil string, cemented with 300 sx. cement, two staged, to set 48 hrs. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company R. OLSEN, Drawer Z. Jal, New Mexico			October 30, 195	6 , 19
(% Sec. and Sec. No.) Langlie—Mattix Lea (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work) We propose to drill to the approximate depth of 3500', set 300' 8 5/8" surface casing with 250 sx. cement to set 24 hrs. 3500' 5½" 15.50% Oil string, cemented with 300 sx. cement, two staged, to set 48 hrs. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company R. OLSEN, Drawer Z. Jal, New Mexico	Well No. 7 is loca	ated 1980 ft. from	- ,	line of sec. 6
Langlie-Mattix (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level isft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work) We propose to drill to the approximate depth of 3500', set 300' 8 5/8" surface casing with 250 sx. cement to set 24 hrs. 3500' 5½" 15.50% Oil string, cemented with 300 sx. cement, two staged, to set 48 hrs. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company R. OLSEN, Drawer Z, Jal, New Maxico Address	SE/4 NW/4	258 37		· · · · ·
The elevation of the derrick floor above sea level isft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme ing points, and all other important proposed work) We propose to drill to the approximate depth of 3500', set 300' 8 5/8" surface casing with 250 sx. cement to set 24 hrs. 3500' 5½" 15.50% 011 string, cemented with 300 sx. cement, two staged, to set 48 hrs. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company R. OLSEN, Drawer Z, Jal, New Maxico			New	
We propose to drill to the approximate depth of 3500', set 300' 8 5/8" surface casing with 250 sx. cement to set 24 hrs. 3500' 5½" 15.50% Oil string, cemented with 300 sx. cement, two staged, to set 48 hrs. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company R. OLSEN, Drawer Z, Jal, New Mexico Address 2811 Liberty Bank Bldg.		t t	veights, and lengths of proposed casing	s; indicate mudding jobs, cemer
Company R. OLSEN, Drawer Z, Jal, New Mexico Address 2811 Liberty Bank Bldg.	8 5/8" surface 5½" 15.50# 0il	drill to the approx	riante depth of 3500', c. cement to set 24 hr	s. 3500'
Address 2811 Liberty Bank Bldg.				perations may be commenced.
ρ .				
			By R. Olas	en e

u. s. government printing office 16-8437-5