

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-1147700
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name WOOLWORTH, GR.3
8. Well No. 001
9. Pool name or Wildcat JALMAT-YATES-SR-QUEEN

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator Phillips Petroleum Company	
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762	
4. Well Location Unit Letter M : 660 Feet From The SOUTH Line and 646 Feet From The WEST Line Section 6 Township 25-S Range 37-E NMPM LEA County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3187.4' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. THIS IS A RULE 118 WELL.
2. NOTE: ALL CEMENT PLUGS WILL BE CLASS "C" MIXED AT 14.8 PPG.
3. MIRU SEIRRA WELL SERVICE, PUMP 50 BBLS WATER DOWN TBG, 80 BBLS WATER DOWN CSG, NU BOPE, COOH W/TBG.
4. GIH W/7" CIBP, SET @ 2800', CIRC CSG W/9.5 PPG MUD-LADEN FLUID.
5. SPOT PLUG NO. 1, 60 SXS, 2800'-2500', COVERS SEVEN RIVERS, YATES & TANSILL.
6. FREEPOINT 7" CSG, NEED TO PULL 1330' OF 7".
7. A. SPOT PLUG NO. 2, 75 SXS, 1380'-1200', COVERS SALT TOP AND 9-5/8" SHOE, WOC & TAG.
B. SPOT PLUG NO. 3, 35 SXS, 500'-400', SAFETY PLUG.
8. PERF 9-5/8" CSG @ 260', PUMP PLUG NO. 4, 175 SXS DOWN 9-5/8" CSG THRU PERFS & BACK TO SURFACE ON 13" & 9-5/8" ANNULUS, LEAVING CSG FULL.
9. CUT OFF CSG, INSTALL MONUMENT MARKER, PERFORM RECLAMATION WORK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Larry M. Sanders TITLE Senior Regulation Analyst DATE 05/09/96
TYPE OR PRINT NAME Larry M. Sanders TELEPHONE NO. (915)368-1488

(This space for State Use)

ORIGINAL SIGNED BY
GARY WINK
FIELD REP. II

MAY 14 1996

APPROVED BY _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: