

Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-11482
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name:  South Langlie Jal Unit
8. Well No.  1
9. Pool name or Wildcat Jal Tansill Yates 7Rivers

<p>SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</p>	
<p>1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other Water Injection Well</p>	
<p>2. Name of Operator Chaparral Energy Inc.</p>	
<p>3. Address of Operator 701 Cedar Lake Blvd, Oklahoma City, OK 73114</p>	
<p>4. Well Location  Unit Letter <u>G</u> : <u>1980</u> feet from the <u>north</u> line and <u>1980</u> feet from the <u>east</u> line  Section <u>7</u> Township <u>25S</u> Range <u>37E</u> NMPM Lea County</p>	
<p>10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3154' GR, 3160' KB</p>	

## 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Note: PBTD is at 3150' with CIBP being set @ 3,200' & capped with 50' cement as reported by TEXACO on Form C-103 dated 6/15/93 requesting TA status and approved by OCD on 6/17/93.

- Set CIBP @ 2,765'
- Run tbg & displace hole with 10 ppg salt gel mud
- Spot cement plug from 2,765' - 2,520' (25 sxs cl "C")
- Spot cement plug from 1,300' - 1,060' (25 sxs cl "C")
- Perforate at 360' and squeeze with 45 sxs cl "C" for 50' in/out plug on surface casing; WOC and tag plug to confirm required fillup
- Spot cement plug from 98' - surface (10 sxs cl "C")
- Install a 4" dry hole marker.

WELL IS SHUT-IN. ALREADY DISCONNECTED 7/25/02

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ralph W. Everett TITLE Operations Engineer DATE 4/26/02

Type or print name Ralph W. Everett

Telephone No. (405) 478-8770

(This space for State use)

APPROVED BY  
Conditions of approval, if any:

ORIGINAL SIGNED BY  
GARY W. WINK  
OC FIELD REPRESENTATIVE II/STAFF MANAGER  
DATE MAY 06 2002