

Indian Agency.....

(SUBMIT IN TRIPLICATE)

Las Cruces
S. Land Office.....
052511-D

Allottee.....

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLease or permit No.....
P.J. Langlie
Jul 21

Lease No.....

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

9-25, 1937

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 8-25-37

NE 8 25S 37E N.M.P.M.

(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Langlie Lea New Mexico

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft. will furnish later

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

In view of the fact that no water whatever was found in Langlie #1, C SE SE Section 8-25S-37E or in Wells #1, C SE SE Section 8-25S-37E above 450', both wells having been drilled with cable tools, it is proposed to eliminate entirely the 13" OD 40' surface casing which was to have been set at 200' according to approved "Notice of Intention to Drill." 9-5/8" casing is to be set at approximately 1200' or on top of salt and cemented with 150% of the calculated amount of cement necessary to cement the string from top to bottom. If cement does not return to surface when plug is pumped down, sufficient cement will be dumped around 9-5/8" casing to furnish finish cementing it back to surface

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company: Anderson-Prichard Oil Corp.Address: Box 1697Hobbs, New MexicoBy W. H. TaylorTitle Manager Prod. Dept.