Form 9-331a	IV.	able	Budget Bureau 42-R358.2.
(Feb. 1951)	(SUBMIT IN TRIPLICATE) UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY		Approval expires 12-31-52.
			Land Office 032511-
SUNDRY	NOTICES AN	D REPORTS OI	N WELLS
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE NOTICE OF INTENTION TO TEST WA NOTICE OF INTENTION TO RE-DRILI NOTICE OF INTENTION TO SHOOT C NOTICE OF INTENTION TO PULL OR NOTICE OF INTENTION TO ABANDON	PLANS TER SHUT-OFF L OR REPAIR WELL R ACIDIZE ALTER CASING	SUBSEQUENT REPORT OF WATER SUBSEQUENT REPORT OF SHOOT SUBSEQUENT REPORT OF ALTER SUBSEQUENT REPORT OF RE-DR SUBSEQUENT REPORT OF ABAND SUPPLEMENTARY WELL HISTORY	TING OR ACIDIZING
(INDIC	ATE ABOVE BY CHECK MARK NAT	JRE OF REPORT, NOTICE, OR OTHEI	R DATA)
		Decen	iber 19
Well No is loca	ted	N line and 2310 ft. fr	om 🙀 line of sec. 🥵
SHA BLA Sec. B (½ Sec. and Sec. No.)	258 37	B Kolle Polle	()
Langlio-Hottix	(Twp.) (Rang	e) (Meridian)	New Mexico
(Field)	(County or Sub	division)	(State or Territory)
The elevation of the derrick	floor above sea level is	3200 ft. approx.	
	DETAILS	OF WORK	
(State names of and expected depths to	o objective sands: show sizes, we	ights and lengths of several	ings; indicate mudding jobs, coment-
		informatic proposed work)	
it is proposed to dri of approximately 3390 Set 10-3/1* or 9-5/2*	. The following (bove described loss pusing and empering d consult with suffi	g program is proposeds

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.				
Company	ANDERSON-PRICHARD OIL CORPORAT	ION		
Address	Res. 2197			
	Hebbs, New MaxLos	By		
		Title District Engineer		

to circulate. Drill through the Detes Sand to approximately 2880', drill stam test the Detes Sand, then set 7" or 5-1/2" easing and compart with 200 sacks. Well will then be drilled to total depth of approximately 3390' and completed in the open hele in the Langlie Pay. Since this well is to be drilled in an area cast of the connervial potech deposits, no means of protecting the selt will be initiated; as per verbal permission from Mr. Hussell, Acting District Engineer.

NTE:

This location was previously staked 330' FEL and 2310' FEL, but because

of a 12,000-welt high line 35' to the south, the location was moved 100'

U. S. GOVERNMENT PRINTING OFFICE 16-8437-4