Pool	Jalmat:			F	ormatio:	nYa	tes		Count v	ن	Form C Revised 12-1	
											3/1/5	
											1	
											as Company	
	g <b>7"</b>											
	g 2}"											
										_	ress13.2	
ate 3	Complet	tion:	11_30_	55	Packe	· r	Sir	gle-Brade	enhead-G.	G. or	G.O. Dual	
	-	_	11-10-			^*		neservo	orr iemb.			
							ATAC CEV					
este	d Through	<b>DDD</b>	<b>75</b> (	Choke)	(Meter)	-			Type Tap	os <b></b>	lange	
		I	low Da				Tubing	Data	Casing I	)ata	<del></del>	
, .	(Line)	(Ori	Mæ) Tice)	Press.	Diff.	Temp.		Temp.	Press.	Temp.		
	Size			psig	h <sub>w</sub>	°F.	psig	°F.	psig	o <sub>F</sub> .	of Flo Hr.	
							612		612	<del> </del>	72	
	4	1.		210	5.29	52	431		149		24	
	<del></del>	1.		2/15	5.76 7.84	_ <del>24</del>	390		405	-	24	
	4		25	215	12.96	<u>58</u> 62	350 229	<del> </del>	369	<del> </del>	21	
									260		<u> </u>	
			_		]	FLOW CAL	CULATION	S				
	Coeffici	ient		Pr	Pressure		Temp.	Gravity	Compress. I		Rate of Flow	
(24-Hot		\ /		<del></del>		Factor Ft		Factor	Factor F <sub>pv</sub>		Q-MCTPD @ 15.025 psi	
		· V W1						$^{ m F}_{f g}$				
<del> </del> -	9.613		<u> 36.58</u>		44.2	1.0078		9608	1.027 351		351	
	9.643		38.55		03.2	1.005		•96 <b>08</b>	1.027		369 426	
	9.643		<u> </u>	2	6 <b>3.2</b> 42 <b>.</b> 2	1.0019 •998		•9608	1.026			
						• • • • • • • • • • • • • • • • • • • •	•	9608	1.022		513	
									<del></del>			
					PRI	ESSURE CA	ALCU ATI	ONS				
Liq	uid Hydro	carbon	Ratio	Dry		cf/bbl.		Speci	fic Gravi	tu Sene	arator Gas <b>0.6</b> 5	
	of Liquid				-	deg.		Specia	fic Gravi	ty Flow	wing Fluid -	
	measured		(1	-e <sup>-s</sup> )				P <sub>c</sub> _6	25.2	P2	390.9	
XX	w		T			7	<del></del>	<del></del>		<del></del>	<del></del>	
•		$P_{\mathbf{t}}^2$	F <sub>C</sub>	<b>ə</b>	$(F_cQ)^2$	(F,	$\left(\frac{Q}{e^{-s}}\right)^2$	P <sub>w</sub> 2	$P_c^2 - P_w^2$	Ca	al. Pu	
	t (psia)					(1	_e-s)	w	C - W	1	$\frac{P_{\mathbf{W}}}{P_{\mathbf{C}}}$	
+	103.2	197.3						13.6	177.3		m	
	363.2	131.9				<del></del>		7),.9	216.0	<u> </u>		
	212.2	58.7				<del></del>		1,6.1	214.8	<del> </del>	_	
$\Box$								74.6	316.3	<del> </del>	<del></del>	
										1	ì	

REMARKS

COMPANY

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- $P_c$ = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_{f}$  Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fny Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .