

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK & Perforate	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Sal, New Mexico
(Place)

June 20, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Three States Natural Gas Company

P.S.B. Sturat
(Company or Operator)

Well No. 1 in M
(Unit)

SW $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 10, T. 25S, R. 37-E, NMPM, Langlin Mattix Pool
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Started 9/13/37, Completed 11/22/37, T.D. 3425', Deepened 12/21/46, T.D. 3465'.

15 $\frac{1}{2}$ " Casing set at 165' - 50 sks. cement
8 5/8" Casing set at 1252' - 100 sks. cement
7" O.D. Casing set at 3168' - 150 sks. cement

Base of Salt - 2500' - Top of Lime 2620' - Brown Lime 3065' - Sandy Gray Lime
3359'-3394' - Showing oil 3388' - Producing from 3359' to 3412' Shot from 3300' to
3417' - 300 qts. Well depleted in this section. Has been on pump since 5/5/48.

Propose to pull rods and tubing, check condition of hole. Run Electric Log. Set cement
retainer in 7" at 3165'. Plug below retainer with 143 sks. of cement. Perforate 7" endeavor-
ing to pick up gas in the lime section between 2620' and 3165' and complete as a gas well.

Approved....., 19.....
Except as follows:

Three States Natural Gas Company
Company or Operator

By Wm. J. G. Fink

Approved
OIL CONSERVATION COMMISSION

Position Division Superintendent
Send Communications regarding well to:

By.....

Name Wm. J. G. Fink

Title.....

Address Box 168 Sal, New Mexico