

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

RECEIVED
JUL 16 1937

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Repelle Oil Company

Hobbs, New Mexico

Company or Operator

Address

F. Stuart "C"

Well No. 3

N/25/2

of Sec. 10

T. 25S

Lease

R. 37E

N. M. P. M.

Hobbs, New Mexico

Field

Loc

County

Well is 350' feet south of the north line and 2510 feet east of the east line of N/25/2 Sec. 10

If State land the oil and gas lease is No.

Assignment No.

If patented land the owner is F. Stuart

Address Hobbs, N.M.

If Government land the permittee is

Address

The Lessee is

Address

Drilling commenced 5/12/37

19

Drilling was completed 7/9/37

19

Name of drilling contractor Hobbs Drilling Co

Address Hobbs, Texas.

Elevation above sea level at top of casing 3113 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3330 to 3354
No. 2, from to
No. 3, from to
No. 4, from to
No. 5, from to
No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 80 to 95 feet.
No. 2, from to 1090 feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
12 1/2"	45	8		347				
8 5/8"	33	8		1800				
7" 9/16"	24	10		3114				
2" Reg. Seamless Tubing				3337				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15 1/2"	12 1/2"	255	300	Balliburton		
10"	8 5/8"	1310	325	Do		
8 1/4"	7" 9/16"	3133	300	Do		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
2 1/2"						

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3354 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 7/12/37 721, 19 100
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

Mr. Edwards

EMPLOYEES Mr. Carl Adams

Mr. Chesney

Driller

Driller

Driller

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Hobbs, New Mexico July 14, 1937

Subscribed and sworn to before me this 15

Place

Date

