

A 10x10 grid with a small 'X' mark in the 4th column and 5th row.

LOCATE WELL CORRECTLY

U. S. LAND OFFICE New Mexico
SERIAL NUMBER 0766
LEASE OR PERMIT TO PROSPECT Blocker

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECOVERED

NOV 17 1954

U. S. GEOLOGICAL SURVEY
WATER RESOURCES DIVISION

LOG OF OIL OR GAS WELL.

Company Anderson-Prichard Oil Corporation Address Box 196, Midland, Texas
Lessor or Tract Blocker Field Justis State New Mexico
Well No. 4 Sec. 13 T. 25S R. 37E Meridian N.M.P.M. County Lea
Location 2310 ft. { N. } of N Line and 1980 ft. { E. } of W Line of Section Elevation 3095
(Derrick floor relative to sea level)
The information given herewith is a complete and correct record of the well and all work done thereon
so far as can be determined from all available records.
Signed: [Signature]
Date November 14, 1958 Title District Superintendent

The summary on this page is for the condition of the well at above date.

Commenced drilling August 26, 1958 Finished drilling November 12, 1958

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

Oil zone (Denote gas by G)

No. 1, from <u>6996</u> to <u>7017</u>	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
13 3/8	48	8rd	H-40	560	Guide				Surface
9 5/8	36	8rd	H-55	399	guide	Eighty feet			Intermediate
7 7/8	23	8rd	H-55	701	guide	Eighty feet			Production
7 7/8	26	8rd	H-55	701					

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
13-3/8	560	450	Pump & Plug		
9-5/8	3390	1775	Pump & Plug		
7"	7019	1050	Pump & Plug		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

[illegible]

TOOLS USED

Rotary tools were used from 0 feet to 7020 feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

DATES

November 14	1958	Put to producing	November 13	1958
The production for the first 24 hours was	104	barrels of fluid of which	50	% was oil; 58%
emulsion; 50% water; and	% sediment.	Gravity, °Bé.	34.6	
If gas well, cu. ft. per 24 hours		Gallons gasoline per 1,000 cu. ft. of gas		
Rock pressure, lbs. per sq. in.				

EMPLOYEES

L. W. Goheen	, Driller	B. R. Haas	, Driller
W. N. Reynolds	, Driller		, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	70	70	Caliche
70	1532	1662	Redbed
1532	2295	763	Anhy & salt
2295	2655	360	Anhy
2655	2945	290	Anhy & Gyp
2945	3148	203	Lime & Anhy
3148	3215	67	Dolomite
3215	5016	1801	Lime
5016	5078	62	Dolomite
5078	6975	1897	Lime
6975	7020	45	Lime & chert
Samples Tops			
			Yates 2340
			Glorieta 4647
			Tubb 5682
			Fusselman 6880

