



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **New Mexico**
Lease No. **0766**
Unit **Blocker**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	

ILLEGIBLE

(MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. **4** is located **2310** ft. from **[N]** line and **1980** ft. from **[W]** line of sec **13**
SE/4 of NW/4 **25S - 37E** **R.M.P.M.**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Justis **Lee** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3100** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill this well to a total depth of 7100'. 13 3/8" surface casing will be set @ approximately 550' and cement circulated to surface.

9 5/8 Intermediate casing will be set @ approximately 3400' with a DV tool at approximately 1000' from surface - sufficient cement to be pumped around bottom of casing to bring cement to DV tool and sufficient cement pumped thru DV tool to bring top of cement to bottom of 13 3/8" casing.

(OVER)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Anderson-Prichard Oil Corp.**

Address **Box 196**
Midland, Texas

By
Title **District Superintendent**

The well to be dually completed in Fusselman (5000') and Brinkard (5000') or Padlock (5000') by running 7" OD casing to total depth with BV tool @ approximately 1400' and sufficient cement around bottom of casing to bring cement to BV tool and sufficient cement thru BV tool to bring cement to bottom of 9 5/8" casing @ approximately 1400' and completed with 2 parallel strings of tubing, each zone produced thru a separate string. If only one zone produces, 5 1/2" casing will be run and sufficient cement around the bottom and thru a BV tool will be run to bring cement to bottom of 9 5/8" casing @ approximately 1400'. Well will be single completed with one string of tubing.