NERGY AND MINERALS DEPARTMENT	•.	
and the second	RVATION DIVISION	
	9. BOX 2088	Form C-103 Revised 10-
FILE SANTA FE, 1	NEW MEXICO 87501	
U.\$.G.\$.		5a. Indicate Type of Lease
LAND OFFICE		State Fee X
OPERATOR		5, State Oil 6 Gas Lease No.
SUNDRY NOTICES AND REPORT	PLUG BACK TO A DIFFERENT RESERVOIR.	
Use Affective for Fermin 2.5 (Form C-101) F	DA SUCH PROPOSALS.)	7. Unit Agreement Name
OIL CAB CTHER-		
Name of Operator		8. Farm or Lease Name
W. K. Byrom	•	McBuffington
Address of Operator	······································	9. Well No.
Box 147 Hobbs, NM88241		1
Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER 1980 FEET FROM THE SOU	th LINE AND 660 FEET FR	Langlie-Mattix
THE East LINC, SECTION 13 TOWNSHIP	255 RANGE 37E NMF	** AIIIIIIIIIIIIIIII
	hether DF, RT, GR, etc.)	
3080 GR.	neiner DP, NT, GA, etc.)	Lea
┑╸╗╺┍┑┍┑┍╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗╗		
Check Appropriate Box To Indica NOTICE OF INTENTION TO:		
NOTICE OF INTENTION TO:	SUBSEQUE	NT REPORT OF:
RAFORM REMEDIAL WORK	X REMEDIAL WORK	ALTERING CASING
MPONARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
JLL OA ALTER CASING	CASING TEST AND CEMENT JOB	
	OTHER	
OTHER		
Describe Proposed or Completed Operations (Clearly state all pertine work) SER RULE 1103. 4-8-85: We will install a ROP for well Co.		
Describe Proposed or Completed Operations (Clearly state all pertine work) SEE RULE 1103. 4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and surface. Cost of the Address of the Address Cost Address	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and surface. Location will be cleaned and and Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Contract Co	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed. Market of NOTIFIED 24 Market of my knowledge and belief.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and surface. Location will be cleaned and and C to Address C to Address	ntrol. We intend to place 20 which will tie back to 4 . The top of the salt (12 casing with water. Place a hors removed.	a 300' plug the 5½" 15.5# csg. 250') will be
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and surface. Location will be cleaned and and O H AMRANA O H AMRANA I hereby certify that the information above is true and complete to the MANAYAMA ORIGINAL SIGNED BY JERRY SEXTON	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed. Market of NOTIFIED 24 Market of my knowledge and belief.	a 300' plug the 5½" 15.5# csg. 250') will be a 10 sx plug and marker
4-8-85: We will install a BOP for well Co over the open hole interval from 3250 - 34 No attempt will be made to pull the casing covered with 140' plug. We will load the surface. Location will be cleaned and and surface. Location will be cleaned and and o to Address o to Address	ntrol. We intend to place 20 which will tie back to to . The top of the salt (12 casing with water. Place a hors removed. Market of NOTIFIED 24 Market of my knowledge and belief.	a 300' plug the 5½" 15.5# csg. 250') will be

RECEIVED

MAR 11 1985