

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO

30-025-11562

5. Indicate Type of Lease

STATE ☒ FEDERAL ☐

6. State Oil & Gas Lease No.

14912

7. Lease Name or Unit Agreement Name

LEARCY McBUFFINGTON

1. Type of Well
Oil Well ☒ Gas Well ☐

OTHER

2. Name of Operator

POGO PRODUCING COMPANY

8. Well No.
#1

3. Address of Operator

P.O. BOX 10340, MIDLAND, TX 79702-0340

9. Pool name or Wellcat

LANGLIE - MATTIX

4. Well Location

Unit Letter L

Feet From The 1980 FS

Line and 660 F W

Feet From The

Section 13

Township 25S

Range 37E

NMPM LEA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3091 RKB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER ☐

SUBSEQUENT REPORT OF

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

WELL BORE 10 3/4 @ 989' CIRCULATE, 8 5/8 @ 1991' CEMENT 250 SACKS- 5 1/2 @ 3101' CEMENT 300 SACKS - OH 3101' - 3267',
PERF 3035' - 3086'

1. TALLY IN HOLE WITH CIBP, SET CIBP @ 2985'; CAP W/ 25 SX SACKS

2. CIRCULATE HOLE W/ 9.5# MUD

3. PUH TO 2500' AND SPOT A 25 SACK PLUG — TAG

4. PUH TO 2041' AND SPOT A 35 SACK PLUG; ~~25 SACKS~~

5. POOH WITH TUBING

6. CUT CASING AT FREE POINT

7. SPOT A 55 SACK PLUG FROM 1039' - 939' — W.D.C. + TAG

8. PLACE A 15 SACK SURFACE PLUG AND P & A MARKER

→ 100' PLUG F/200' - 100' W.D.C. + TAG

CONDITIONS OF APPROVAL

All pits must be lined with plastic

All shoe plugs, stub plugs & cement plugs above perforations must be tagged

All cement plugs pumped minimum 25 sxs & be minimum 100 feet

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

AGENT

DATE

2/27/02

TYPE OR PRINT NAME

HOWARD BOATRIGHT

TELEPHONE NO. 915-570-5382

(This space for State Use)

APPROVED BY

Larry W. Wink

ORIGINAL SIGNED BY

LARRY W. WINK

FIELD TITLE MANAGER / STAFF MANAGER

CONDITIONS OF APPROVAL, IF ANY

MAR 13 2002

DATE