

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Oct 11 10 21 AM '65

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Gulf Oil Corporation 3. Address of Operator P. O. Box 980, Kermit, Texas 4. Location of Well UNIT LETTER K , 1650 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 13 TOWNSHIP 25S RANGE 37E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3090' DF	7. Unit Agreement Name 8. Farm or Lease Name Learcy McBuffington 9. Well No. 9 10. Field and Pool, or Wildcat Justis Fusselman & Montoya 12. County Lea
--	---

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☒ **Plug off lower Montoya, recomplete in upper Montoya**

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out Model D packer at 6915'. Ran junk basket and gauge ring below perf at 7052'. Set CI Baker cement retainer at 6980' and squeezed perf 7004-7052' w/25 sx reg. cmt., squeezed to 1000 psi. Set Model D packer on Wire line at 6910'. Ran 227 jts (6927) 2 7/8" CS hydrill tbg set at 6940', latched into Model D packer at 6910' w/8 points tension (Montoya). Ran 240 jts (6865') 2 3/8" EUE 8 TBG set at 6874' w/7 points tension (Fusselman). Ran rods and pump in Montoya. Swabbed (Fusselman) 108 BO and 114 BW in 24 hrs end 7:00 A.M., 9-30-65. Montoya pumped 95 BO & 210 BW, 9 MCF, GOR 96, 12 x 76" SPM in 24 hrs end 7:00 A.M. 10-6-65.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M. M. Whitaker TITLE Area Engineer DATE 10-7-65

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: