

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool Jalmat Formation Iates County Lea
Initial Annual Special X Date of Test 2-25/3-1 1957
Company El Paso Natural Gas Company Lease Prichard Well No. 1
Unit N Sec. 15 Twp. 25 Rge. 37 Purchaser El Paso Natural Gas Company
Casing 5 1/2 Wt. 14.0 I.D. Set at 2980 Perf. To
Tubing 2 Wt. 4.7 I.D. Set at 2939 Perf. To
Gas Pay: From 2789 To 2934 L 2939 xG 0.645 -CL 1896 Bar.Press. 13.2
Producing Thru: Casing Tubing X Type Well Single
Date of Completion: 7-12-56 Packer None Single-Bradenhead-G. G. or G.O. Dual
Reservoir Temp.

OBSERVED DATA

Tested Through (~~Prover~~) (~~Orifice~~) (Meter)Type Taps Flange

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Orifice) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						625		625		72
1.	4	1.000	535	12.96	75	612		615		24
2.	4	1.000	555	16.81	82	607		610		24
3.	4	1.000	546	43.56	79	595		600		24
4.	4	1.000	525	81.00	78	545		586		24
5.										

FLOW CALCULATIONS

No.	Coefficient (Flg) (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	6.135	84.27		.9859	.9645	1.050	517
2.	6.135	97.72		.9795	.9645	1.051	596
3.	6.135	156.04		.9822	.9645	1.050	952
4.	6.135	208.76		.9831	.9645	1.050	1,275
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio Dry cf/bbl.
Gravity of Liquid Hydrocarbons deg.
F_c Measured (1-e^{-s})

Specific Gravity Separator Gas 0.645
Specific Gravity Flowing Fluid
P_c 638.2 P_c 407.3

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.	625.2	390.9				394.6	12.7		.98
2.	620.2	384.6				388.4	18.9		.97
3.	608.2	369.9				376.0	31.3		.95
4.	558.2	311.6				359.0	48.3		.87
5.									

Absolute Potential: 5,400 MCFPD; n .68COMPANY El Paso Natural Gas CompanyADDRESS Box 1384, Jal, New MexicoAGENT and TITLE R. T. Wright - Petroleum EngineerWITNESSED Karl G. SmithCOMPANY El Paso Natural Gas Company

REMARKS

JAL
ENGINEER

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressibility factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .