Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

OTICE OF INTENTION TO TEST CASING SHUT-OFF	8-5/8*	NOTICE (F INTENTION ICALLY TREA	TO SH	OOT OR	
OTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING				
OTICE OF INTENTION TO REPAIR WELL		NOTICE (of intention	TO PL	UG WEL	JL
OTICE OF INTENTION TO DEEPEN WELL						
	Hobbe	N Mer	January	Sth .	1958	
	40005	Place	- 411441	· · · ·		Date
IL CONSERVATION COMMISSION, anta Fe, New Mexico. entlemen:						
ollowing is a notice of intention to do certain wor Ellict		ibed below a		2		SE/4
Company or Operator 27E	Lease		Well No Langlie		i	in
Sec, T, R	, N.	M. P. M.,				Field
Lea County.						
teel Casing set in Anhydrite at 122	2' cemen	d Thread ted with	South Per 350 sack	an Gra	ade "C' Loquag	" Seamless el Cement a
Steel Casing set in Anhydrite at 122 of sacks Neat Cement by Halliburton.	2' cemen	ted with	350 sack	an Gre	ade "C Lequag	" Seamless al Cement a
Steel Casing set in Anhydrite at 122 of sacks Neat Cement by Halliburton.	2' cemen	ted with	350 sack	n Gre	ade "C' Acquag	" Seamless al Cement a
teel Casing set in Anhydrite at 122 0 sacks Neat Cement by Halliburton.	2' cemen	ted with	350 sack	4, 1	lequag	el Cement a
teel Casing set in Anhydrite at 122 0 sacks Neat Cement by Halliburton.	2' cemen	ted with	350 sack	4, 1	lequag	el Cement a
teel Casing set in Anhydrite at 122 0 sacks Neat Cement by Halliburton. ropose to drill plug and test 6:30	2' cemen	ted with	350 sack	4, 1	lequag	el Cement a
o sacks Neat Cement by Halliburton. ropose to drill plug and test 6:30	2' cemen	ted with	350 sack	46	Acquag	el Cement a
o sacks Neat Cement by Halliburton. ropose to drill plug and test 6:30	2' cemen	ted with	350 sack	ny or Op	Acquag	el Cement a
pproved	AM Janua	ted with ry 9th,	350 sack	ny or Op	Acquag	el Cement a
Steel Casing set in Anhydrite at 122 to sacks Neat Cement by Halliburton. Propose to drill plug and test 6:30	AM Janua	ted with ry 9th, By Q Q	350 sack	ny or Op	dequag	al Cement a
Steel Casing set in Anhydrite at 122 so sacks Neat Cement by Halliburton. Propose to drill plug and test 6:30	2' cemen	ry 9th, By @@ Position	Compa	ny or Op	dequag	al Cement a
January 7th, 1938, Cemented 9-5/8* 0 Steel Casing set in Anhydrite at 122 50 sacks Neat Cement by Halliburton. Propose to drill plug and test 6:30 pproved	Av Janua	ted with ry 9th, By Q Q Position Ser	Compa	ny or Op Supt. tions re	dequag	al Cement a