

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Recomplete	X	NOTICE OF INTENTION (OTHER) Repr. Csg. Leak	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

May 18, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **J. A. Elliott**

Gulf Oil Corporation
(Company or Operator)

Well No. **1** in **P**
(Unit)

SW $\frac{1}{4}$ **SW** $\frac{1}{4}$ of Sec. **15**, T. **25-S**, R. **37-E**, NMPM., **Langlie Matrix** Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to abandon oil zone, repair casing leak and recomplete in the
Jalnet Gas Pool as follows:

1. Pull tubing. Run radioactivity survey.
2. Set cast iron bridge plug in base of 5-1/2" casing with 1 sack cement on top.
3. Run HRC tool. Locate leak in 5-1/2" casing. Attempt to circulate out 5-1/2" - 7-5/8" annulus.
4. Set cement retainer above leak. Squeeze cement below retainer.
5. W.C.
6. Pressure test casing. If O.K. drill out cement and retainer. Pressure test 5-1/2" casing again.
7. Perforate gas zone as determined from radioactivity survey.
8. Wash perforations with 500 gallons mud acid. Swab and test.
9. If warranted, treat perforations with 17,000 gallons oil, 1# sand per gallon.
10. Swab and test.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By *A. G. Starkey*
Title.....

Gulf Oil Corporation
Company or Operator

By *S. J. Jay*

Position **Area Supy. of Prod.**

Send Communications regarding well to:

Name **Gulf Oil Corporation**

Address **Box 2167, Hobbs, N. M.**