

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate question(s) to be followed by (1). **SUBMIT IN TRIPLICATE**

No. 1, from 3338 to 3544 No. 4, from _____ to _____

No. 2, from 3362 to 3372 No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

[illegible]

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12"	8-8/8	340'	125	Halliburton		
8-5/4"	8-1/2"	3164'	500	"		

Heaving plug—Material.....Length.....Depth Set.....

Adapters—Material.....Size.....

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 3380 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

Put to producing....., 19 **36**

The production of the first **24** hours was..... barrels of fluid of which **100%** was oil;..... %

emulsion;..... % water; and..... % sediment. Gravity, Be.....

If gas well, cu. ft. per 24 hours..... Gallons gasoline per 1,000 cu. ft. of gas.....

Rock pressure, lbs. per sq. in.....

John Martin, Driller C. L. Whigham, Driller
R. F. Ferguson, Driller

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 21st day of June, 1934.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	200	200	Sand & shells
200	360	160	Shale & shells
360	430	90	Sand & shale
430	600	150	Shale & shells
600	740	140	Red rock & red bed
740	925	185	Red rock & red shale
925	1060	135	Shale & shells
1060	1190	130	Anhydrite
1190	1360	170	Salt & anhydrite
1360	2440	1080	Salt & anhydrite
2440	2440	0	Line
2440	2510	70	Lime, anhydrite & gypsum
2510	2582	72	Anhydrite & gypsum
2582	2617	35	Line
2617	2669	52	Anhydrite, sandy shale & shale
2669	2770	101	Shale & anhydrite
2770	2838	68	Lime & anhydrite
2838	2878	40	Lime & gypsum
2878	2970	92	Lime & anhydrite
2970	3109	39	Line
3109	3182	73	Lime & anhydrite
3182	3213	31	Lime & gypsum
3213	3283	70	Brown lime
3283	3291	8	Line
3291	3294	3	Hard lime
3294	3302	8	Line
3302	3373	71	Broken sand & lime
3373	3380	7	Line
3380	3380	0	Total depth.