

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO.  
30-025-11614

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.  
408175

7. Lease Name or Unit Agreement  
Name:

SOUTH LANGLIE JAL UNIT

8. Well No.

#16

9. Pool name or Wildcat

JAL TANSILL YATES 7 RIVERS

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other WATER INJECTION WELL

2. Name of Operator

CHAPARRAL ENERGY, INC.

3. Address of Operator

701 CEDAR LAKE BLVD., OKLAHOMA CITY, OK 73114

4. Well Location

Unit Letter \_\_\_\_\_ G: 2310 feet from the NORTH line and 1980 feet from the EAST line

Section 18 Township 25S Range 37E NMPM LEA County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3115 RKB, 3105 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐


OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. SET CIBP @ 3041'. - TAG
2. RUN TUBING AND DISPLACE HOLE WITH SALT GEL MUD.
3. SPOT CEMENT PLUG FROM 2610' - 3040' (45 SX "C").
4. SPOT CEMENT PLUG FROM 1100' - 1340' (25 SX "C").
5. SPOT CEMENT PLUG FROM 96' TO SURFACE (10 SX "C").
6. INSTALL A 4" DRY HOLE MARKER.

→ 8 5/8 CSG SHOE 330' PERF @ 380' 50' OUTSIDE + INSIDE TAG

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ralph W. Everett TITLE OPERATIONS ENGINEER DATE 12/28/01

Type or print name RALPH W. EVERETT

Telephone No. (405) 478-8770 ext. 1278

(This space for State use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of approval, if any: