NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

He ras strate acc

MISCELLANEOUS REPORTS ON WELLS IN 7:37

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON CLEAN OUT (Other) & FRACTURE	<u>x</u>
	March 25, 1955	Midland, Texas	
Following is a report on the worl	done and the results obtained under the heading	noted above at the	
SOUTHERN CALIFORNIA	PETROLEUM CORPORATION	Vosburg (Lease)	
Company Rig & Eakin	Reverse Circulatorwell No. 1	in the	3,
T25S, R37E, NMPM.,	Ianglie_MattixPool,	Lea Co	ounty.
The Dates of this work were as follows:	March 16 - 24, 19	55	
Notice of intention to do the work (we	(was not) submitted on Form C-102 on	(Cross out incorrect words)),
and approval of the proposed plan (wa	s) (was not) obtained.		
	well had become sub-allowa		_
cleaned out w/6-1/8" of iron clips and mag cuttings to 3330'. I treated open hole 316 Max. press. 4100#, mi 6.3 B/min; 3 hrs. for Lowered thg. & rever w/ seating nipple @ anchor on top of pkr	bit by reverse circulation, gnesium from McCullough "expans 2" tbg. tb 3181' & set 68-3330' w/10,000 gals. & 12 inimum treating press. 29506 r pressure to bleed to forms sed out 16' frac sand 3314-33288', 7" Guiberson KV-8 pkg., safety joing 6 3062' and	cendable" jet gun & forma kuib. KV-8 pkr. @ 2961' a 2,000# Dowell Sandfrac 3/ 4; average injection rat ation from 800# to gero. 330'. Landed tbg. @ 332 c. @ 3100' & H-1 hydrauli Garrett Circulating Value	nd /23/55 e
at 2905'. Swabbed off Queen oi	1 zone, 3/24 - recovering 10 n stimulation will be filed rwin SO.CAL.FET.COR	after adequate testing. Prod. Foreman	r e