

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

9-2-1952

(Date)

Midland, Texas

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Culbertson &amp; Irwin, Inc.

(Company or Operator)

Vosburg

(Lease)

Hillman-Caldwell

(Contractor)

Well No. 1 in the NE 1/4 SE 1/4 of Sec. 18

T. 25S, R. 37E, NMPM, Langlie-Mattix Pool, Lea County.

The Dates of this work were as follows: 8-24-52

Notice of intention to do the work (was) (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_\_,  
(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 7" 20# & 23# J-55 casing with HOWCO float collar and float shoe to 3168' and cemented w/200 sax. Pumped 100 sax cement thru HOWCO 2-stage tool at 1052'. Let set 48 hrs. Applied 900 psi for 15 min. to casing before drilling out top plug. Test o.k. Tested csg. w/900 psi for 30 min. after drilling out top plug. Test o.k. Shot 4-1/2" holes w/ Johnson shoot-n-test @ 2770', and set hookwall pkr. @ 2740'. Had immediate fair blow to very strong w/gas to the surface in 10 min. Tool open 1 hr. 30 min. Recovered 175' gas-cut drilling fluid. Charts showed: Hydrastatic mud weight - 1415 psi  
Flowing pressure - 45 psi.,

Witnessed by: Robert W. Mannon (Name) Culbertson & Irwin, Inc. (Company) Pet. Engr. (Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Robert W. Mannon

Position: Pet. Engr.

Representing: Culbertson &amp; Irwin, Inc.

Address: Box 1071, Midland, Texas

Engineer District 1

(Title)

(Date)