SOUTHERN CALIFORNIA PETROLEUM CORPORATION

VOSBURG #2

10-13-52 DST #1 2885-3010' 8-3/4" open hole.

Ran M. O. Johnson DST on 3-1/2" drill pipe w/125' of solid tail pipe, single side wall packer w/bottom at 2885'. Tooldopen at 5 P:M. Immediate medium steady blow decreasing to weak steady for 45 min. open period. Gas to surface in 14 minutes. Closed shut-in tool for 15 minutes. Pulled tester loose at 6 P:M.

Recovered \$20' oil and gas-cut mud wless than 5% free oil noticed. F.P. 125# even SIP 300# and still increasing.

W. HL Mannon

ANNERS OF DEPENDENT OF TAKES OF THE ASSA

Environmental de la construcción de la

10-13-53-58 10200 /1 10 1020 /1 10 1020 /1 10 1020

% Start. G. Spinste Stat on 3-1/s" doill plys w/125* of artif red bigs. Siskin with world backer w/bottom at 2985*. Inclusions of 30.00. Ecoclete median attest olde secressing to see obselve for 45 min. or a parted. The F surface for 11 member. Gloned when it had for 1000 and set of 10000 attest.

Leonovano 2201 -11 na jus-opt and af no than 59 Crea air - airsa 1. . 1955 - ever 217 - 2008 arth. Sanatar .

toress the

.