NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe. New Mexico

Santa Fe, New Mexico	training in	. '	00(
MISCELLANEOUS NOTICES	Control of the second		

Box 708, Roswell, H. M.

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See addi-

	Indicate Nature of Notice by Checkin	ng Below	
Sotice of Intention o Change Plans	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
OTICE OF INTENTION O PLUG WELL	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
OTICE OF INTENTION O SQUEEZE	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
otice of Intention OGUN Perforate	Notice of Intention (Other)	Notice of Intention (Other) TO THEAT	x
IL CONSERVATION COMMI		September 13	11.955
entlemen:	(Place)	(Date)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Following is a Notice of Inter	ntion to do certain work as described below at the	LECHARD OIL COMPANY	•••••
(Company	or Operator)		
	16 , T 256 , R 37E ,N		
, , , , , , , , , , , , , , , , , , , ,			
	COHHIV		
	·	AN OF WORK	
(FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A		
	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES A	AND REGULATIONS)	
	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES AS - TD 3790 (Wtr) - Plugged back	and regulations) to 3018" (8 Sx mad & 19 Sx	: Cement,
	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES A	and regulations) to 3018" (8 Sx mad & 19 Sx	: Cement,
9-4-55 to 9-12-55	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES AS - TD 3790 (Wtr) - Plugged back work done by	and regulations) to 3018" (8 Sx mad & 19 Sx Halliburton.	_
	FULL DETAILS OF PROPOSED PLAFOLLOW INSTRUCTIONS IN THE RULES AS - TD 3790 (Wtr) - Plugged back	and regulations) to 3018" (8 Sx mad & 19 Sx Halliburton.	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55 PROPOSE TO TREAT	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4 - (10,000 gallons sand treatment	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber t - Halliburton)	
9-4-55 to 9-12-55 9-13-55 PROPOSE TO TREAT	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4 - (10,000 gallons sand treatment	to 3018" (8 Sx mud & 19 Sx Halliburton. shots per foot (Schlumber	_
9-4-55 to 9-12-55 9-13-55	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4 - (10,000 gallons sand treatment	to 3018" (8 Sx mad & 19 Sx Halliburton. shots per foot (Schlumber t - Halliburton)	_
9-4-55 to 9-12-55 9-13-55 PROPOSE TO TREAT	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4 - (10,000 gallons sand treatment By	to 3018" (8 Sx mad & 19 Sx Halliburton. shots per foot (Schlumber t - Halliburton)	
9-4-55 to 9-12-55 9-13-55 PROPOSE TO TREAT	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4 - (10,000 gallons sand treatment By	to 3018" (8 Sx mad & 19 Sx Halliburton. shots per foot (Schlumber t - Halliburton) RD OIL COMPANY ORIGINAL SIG	eger) SNED BY ONARD
9-4-55 to 9-12-55 9-13-55 PROPOSE TO TREAT	FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A 5 - TD 3790 (Wtr) - Plugged back work done by - Perforated from 2966-3016', 4 - (10,000 gallons sand treatment By	to 3018" (8 Sx mad & 19 Sx Halliburton. shots per foot (Schlumber t - Halliburton) RD OIL COMPANY ORIGINAL SIGNAL SIGN	eger) SNED BY ONARD